




PRESTATIEVERKLARING

REYNAERS DEUREN – MASTERLINE 8

Nr. R-02 **d.d. 01/07/2026**

Productnaam	Deuren vervaardigd uit de profielsystemen : Reynaers Masterline 8			
Type aanduiding	<5.1> Naar binnen draaiende deuren met enkele vleugel en drempelprofiel <5.2> Naar binnen draaiende deuren met enkele vleugel en tochttribber <5.3> Naar buiten draaiende deuren met enkele vleugel en drempelprofiel <5.4> Naar buiten draaiende deuren met enkele vleugel en tochttribber <5.5> Naar binnen draaiende deuren met dubbele vleugel en drempelprofiel <5.6> Naar binnen draaiende deuren met dubbele vleugel en tochttribber <5.7> Naar buiten draaiende deuren met dubbele vleugel en drempelprofiel <5.8> Naar buiten draaiende deuren met dubbele vleugel en tochttribber <5.9> Pivoterende deuren <5.10> Pivoterende deuren XL			
Toepassing	Reynaers deuren Masterline 8 voor toepassing in woningen en utiliteitsgebouwen zonder brand- en rookwerende eigenschappen.			
Naam en contactadres fabrikant	raamSELECT NV Merksplassesteenweg 18 2310 Rijkvorsel			
Naam en contactadres gemachtigde	Niet van toepassing			
Systeem voor de beoordeling en verificatie van de prestatiebestendigheid	AVCP 3			
Activiteit van de aangemelde certificatie-instantie volgens NBN EN 14351-1:2006+A2:2016	ID	Name	Address	Country
	0074	CENTRE D'EXPERTISE DU BÂTIMENT ET DES TRAVAUX PUBLICS	Domaine De Saint-Paul – 102, Route de Limours 78471 Saint-Remy-Les-Chevreuse Cedex	France
	0336	TÜV RHEINLAND NEDERLAND	Westervoortsedijk 73 6827 AV Arnhem	Netherlands
	0432	MATERIALPRÜFUNGSAMT NORDRHEIN-WESTFALEN	Auf den Thronen 2 59597 Erwitte	Germany
	0679	CENTRE SCIENTIFIQUE ET TECHNIQUE DU BÂTIMENT	84, Avenue Jean Jaurès Champs-sur-Marne F-77447 Marne-la-Vallée Cedex 2	France
	0744	SOCOTEC	Les Quadrants – 3,Avenue du Centre – Guyancourt 78182 St-Quentin en Yvelines	France
	0749	BELGIAN CONSTRUCTION CERTIFICATION ASSOCIATION	Aarlenstraat 53 1040 Brussel	Belgium
	0757	IFT ROSENHEIM	Theodor-Giell-Strasse 7-9 83026 Rosenheim	Germany
	0845	DANISH INSTITUTE OF FIRE AND SECURITY TECHNOLOGY	Jernholmen, 12 2650 Hvidovre	Denmark
	0960	SKG-IKOB	Poppenbouwing 56 4191 NZ Geldermalsen	Netherlands
	1136	BELGIAN BUILDING RESEARCH INSITUTE	Lombardstraat 42 1000 Brussel	Belgium
	1234	EFACTIS NEDERLAND	Brandpuntlaan Zuid 16, Postbus 554 2665 ZN Bleiswijk	Netherlands
	1288	WINTech ENGINEERING LIMITED	Halesfield 2 Telford,Shropshire TF7 4QH	United Kingdom
	1309	PRÜFINSTITUT SCHLÖSSER UND BESCHLÄGE, VELBERT	Wallstrasse 41 42551 Velbert	Germany
	1488	INSTYTUT TECHNIKI BUDOWLANEJ	ul. Filtrawa 1 00-611 Warszawa	Poland
	1671	PEUTZ	Lindenlaan 41, Molenhoek PO Box 66 6585 ZH MOOK	Netherlands
	1749	TNO DEFENCE, SECURITY AND SAFETY	Lange Kleiweg 137, Postbus 45 2280 AA Rijswijk	Netherlands
	1769	UNIVERSITY OF GENT	Sint-Pietersnieuwstraat 41 9000 Gent	Belgium
	1812	EFACTIS FRANCE	ZI. Les Nappes 149, route du Marc 38630 Les Aveniers Veyrins-Thuellin	France
	2211	INSTITUTO DE INVESTIGAÇÃO E DESENVOLVIMENTO TECNOLÓGICO PARA A CONSTRUÇÃO, ENERGIA, AMBIENTE E SUSTENTABILIDADE	Rua Pedro Hispano Pólo II da Universidade de Coimbra 3030-289 Coimbra	Portugal
	2434	CENTRUM TECHNIKI OKRĘTOWEJ	ul. Szczecińska 65 80-392 Gdańsk	Poland
	2509	DMT	Hermann-Kemper-Str. 12a 43899 Solingen	Germany


Namens het management van	Datum	Naam	Handtekening
raamSELECT NV	01/07/2026	Stijn Hoskens	

<5.1> NAAR BINNEN DRAAIENDE DEUREN MET ENKELE VLEUGEL EN DREMPELPROFIEL



raamSELECT NV
Merksplassesteenweg 18
2310 Rijkevorsel

Aangegeven prestaties volgens
NBN EN 14351-1:2006+A2:2016




Characteristic			Performance		Notified body - Report		Tested size [mm]	
Essential characteristics								
EN 14351-1	4.2	Resistance to wind load	C2 (800 Pa)		[0960] – 20.01457		1400x3000	
	4.5	Watertightness	8A (450 Pa)		[0960] – 20.01457		1400x3000	
	4.6	Dangerous substances	In the materials delivered by Reynaers, no dangerous substances as indicated in hEN 14351-1 are used.					
	4.7	Impact resistance	5 ⁽¹⁾		[0960] – 09.1168 ⁽²⁾		604x1739	
	4.8	Load-bearing capacity of safety devices	Pass		[0960] – 20.00934		1400x3000	
	4.9	Height & width	See 6					
	4.11	Acoustic performance	Glass: 34 (-1;-4) 41 (-2;-4) 50 (-2;-8)	Doors: 37 (-2;-5) 39 (-2;-4) 43 (-2;-4) ⁽³⁾	[0757] – 18-000457-PR03 (GAS-C01-04-en-01)		889~1279 x 2062~2452	
	4.12	Thermal transmittance	Ud to be calculated in function of the project. Pre-calculated U-values for dimensions 1230x2180mm can be found in the Uf-value tables. Uf-values are calculated under certification of BCCA: certificate BPCB-420-72-10077/2.					
	4.13	Radiation properties	These properties must be evaluated by the CE-label of the glass					
	4.14	Air permeability	3		[0960] – 20.01457		1400x3000	

Non-essential characteristics					
EN 14351-1	4.4.1	Reaction to fire	Anodized: A1 Painted: A2 Gaskets: E	EC decision 96/603/EC [1812] - EFR-21-001664A [0432] - 230006500-6	
	4.16	Operating forces	1	[0960] - 18.00012.2	1400x3000, 256 kg
	4.17	Mechanical strength	4	[0960] - 20.00934	1400x3000, 250 kg
	4.18	Ventilation	npd		
	4.19	Bullet resistance (BP version)	npd		
	4.20	Explosion resistance	npd		
	4.21	Resistance to repeated opening and closing	8 (1.000 000)	[0960] - 18.00012.2 [0960] - 22.00088.1	1400x3000, 256 kg 1400x3000, 160 kg
	4.22	Behaviour between different climates	npd		
	4.23	Burglar resistance (AP version)	RC2 RC3	[1309] - 45-2/25 [1136] - EF-24-431-01	See report

De prestaties van de producten die met bovenstaande unieke identificatiecodes zijn aangeduid, zijn in overeenstemming met de betreffende opgegeven prestaties. Deze prestatieverklaring wordt afgegeven onder de uitsluitende verantwoordelijkheid van raamSELECT

Voor en namens de fabrikant ondertekend door :


Naam en functie	Plaats en datum van afgifte	Handtekening
Stijn Hoskens (directeur)	01/07/2026	

<5.2> NAAR BINNEN DRAAIENDE DEUREN MET ENKELE VLEUGEL EN TOCHTRUBBER



raamSELECT NV
Merksplassesteenweg 18
2310 Rijkevorsel

Aangegeven prestaties volgens
NBN EN 14351-1:2006+A2:2016




Characteristic			Performance		Notified body - Report	Tested size [mm]
Essential characteristics						
EN 14351-1	4.2	Resistance to wind load	C2 (800 Pa)		[0960] – 21.00162 rev A	1352x2207
	4.5	Watertightness	5B (200 Pa)		[0960] – 21.00162 rev A	1352x2207
	4.6	Dangerous substances	In the materials delivered by Reynaers, no dangerous substances as indicated in hEN 14351-1 are used.			
	4.7	Impact resistance	5 ⁽¹⁾		[0960] – 09.1168 ⁽²⁾	604x1739
	4.8	Load-bearing capacity of safety devices	Pass		[0960] – 20.00934	1400x3000
	4.9	Height & width	See 6			
	4.11	Acoustic performance	Glass: 34 (-1;-4) 41 (-2;-4) 50 (-2;-8)	Doors: 33 (-2;-5) 34 (-1;-3) 35 (-1;-2)	[0757] – 18-000457-PR03 (GAS-C01-04-en-01)	889~1200 x 2062~2942
	4.12	Thermal transmittance	Ud to be calculated in function of the project. Pre-calculated U-values for dimensions 1230x2180mm can be found in the Uf-value tables. Uf-values are calculated under certification of BCCA: certificate BPCB-420-72-10077/2.			
	4.13	Radiation properties	These properties must be evaluated by the CE-label of the glass			
	4.14	Air permeability	3		[0960] – 21.00162 rev A	1352x2207

Non-essential characteristics					
EN 14351-1	4.4.1	Reaction to fire	Anodized: A1 Painted: A2 Gaskets: E	EC decision 96/603/EC [1812] - EFR-21-001664A [0432] – 230006500-6	
	4.16	Operating forces	1	[0960] – 18.00012.2	1400x3000, 256 kg
	4.17	Mechanical strength	4	[0960] – 20.00934	1400x3000, 250 kg
	4.18	Ventilation	npd		
	4.19	Bullet resistance (BP version)	npd		
	4.20	Explosion resistance	npd		
	4.21	Resistance to repeated opening and closing	8 (1.000 000)	[0960] – 18.00012.2 [0960] – 22.00088.1	1400x3000, 256 kg 1400x3000, 160 kg
	4.22	Behaviour between different climates	npd		
	4.23	Burglar resistance (AP version)	RC2 RC3	[1309] – 45-2/25 [1136] – EF-24-431-01	See report

De prestaties van de producten die met bovenstaande unieke identificatiecodes zijn aangeduid, zijn in overeenstemming met de betreffende opgegeven prestaties. Deze prestatieverklaring wordt afgegeven onder de uitsluitende verantwoordelijkheid van raamSELECT

Voor en namens de fabrikant ondertekend door :


Naam en functie	Plaats en datum van afgifte	Handtekening
Stijn Hoskens (directeur)	01/07/2026	

<5.3> NAAR BUITEN DRAAIENDE DEUREN MET ENKELE VLEUGEL EN DREMPELPROFIEL



raamSELECT NV
Merksplassesteenweg 18
2310 Rijkevorsel

Aangegeven prestaties volgens
NBN EN 14351-1:2006+A2:2016




Characteristic			Performance		Notified body - Report		Tested size [mm]	
Essential characteristics								
EN 14351-1	4.2	Resistance to wind load	C2 (800 Pa) C2 (800 Pa) C4 (1600 Pa)		[0960] – 21.00162 Rev A [0960] – 20.01458 [0960] – 24.00681		1400x2600 1400x3000 935x2633	
	4.5	Watertightness	9A (600 Pa) 7A (300 Pa) 7A (300 Pa)		[0960] – 21.00162 Rev A [0960] – 20.01458 [0960] – 24.00681		1400x2600 1400x3000 935x2633	
	4.6	Dangerous substances	In the materials delivered by Reynaers, no dangerous substances as indicated in hEN 14351-1 are used.					
	4.7	Impact resistance	5 ⁽¹⁾		[0960] – 09.1168 ⁽²⁾		604x1739	
	4.8	Load-bearing capacity of safety devices	Pass		[0960] – 20.00710.1		1400x3000	
	4.9	Height & width	See 6					
	4.11	Acoustic performance	Glass: 34 (-1;-4) 41 (-2;-4) 50 (-2;-8)	Doors: 37 (-2;-5) 39 (-2;-4) 43 (-2;-4) ⁽³⁾	[0757] – 18-000457-PR03 (GAS-C01-04-en-01)		889~1279 x 2062~2452	
	4.12	Thermal transmittance	Ud to be calculated in function of the project. Pre-calculated U-values for dimensions 1230x2180mm can be found in the Uf-value tables. Uf-values are calculated under certification of BCCA: certificate BPCB-420-72-10077/2.					
	4.13	Radiation properties	These properties must be evaluated by the CE-label of the glass					
	4.14	Air permeability	4 3 4		[0960] – 21.00162 Rev A [0960] – 20.01458 [0960] – 24.00681		1400x2600 1400x3000 935x2633	

Non-essential characteristics					
EN 14351-1	4.4.1	Reaction to fire	Anodized: A1 Painted: A2 Gaskets: E	EC decision 96/603/EC [1812] - EFR-21-001664A [0432] - 230006500-6	
	4.16	Operating forces	1	[0960] - 20.01458	1400x3000, 180 kg
	4.17	Mechanical strength	4	[0960] - 20.00710.1	1400x3000, 250 kg
	4.18	Ventilation	npd		
	4.19	Bullet resistance (BP version)	npd		
	4.20	Explosion resistance	npd		
	4.21	Resistance to repeated opening and closing	8 (1.000 000)	[0960] - 20.00710.1	1400x3000, 250 kg
	4.22	Behaviour between different climates	npd		
	4.23	Burglar resistance (AP version)	RC2 RC3	[1309] - 45-2/25 [1136] - EF-24-431-01	See report

De prestaties van de producten die met bovenstaande unieke identificatiecodes zijn aangeduid, zijn in overeenstemming met de betreffende opgegeven prestaties. Deze prestatieverklaring wordt afgegeven onder de uitsluitende verantwoordelijkheid van raamSELECT

Voor en namens de fabrikant ondertekend door :

Naam en functie	Plaats en datum van afgifte	Handtekening
Stijn Hoskens (directeur)	01/07/2026	

<5.4> NAAR BUITEN DRAAIENDE DEUREN MET ENKELE VLEUGEL EN TOCHTRUBBER



raamSELECT NV
Merksplassesteenweg 18
2310 Rijkevorsel

Aangegeven prestaties volgens
NBN EN 14351-1:2006+A2:2016




Characteristic			Performance		Notified body - Report		Tested size [mm]	
Essential characteristics								
EN 14351-1	4.2	Resistance to wind load	C2 (800 Pa)		[0960] – 21.00162 rev A		1352x2204	
	4.5	Watertightness	4A (150 Pa)		[0960] – 21.00162 rev A ⁽³⁾		1352x2204	
	4.6	Dangerous substances	In the materials delivered by Reynaers, no dangerous substances as indicated in hEN 14351-1 are used.					
	4.7	Impact resistance	5 ⁽¹⁾		[0960] – 09.1168 ⁽²⁾		604x1739	
	4.8	Load-bearing capacity of safety devices	Pass		[0960] – 20.00710.1		1400x3000	
	4.9	Height & width	See 6					
	4.11	Acoustic performance	Glass: 34 (-1;-4) 41 (-2;-4) 50 (-2;-8)	Doors: 33 (-2;-5) 34 (-1;-3) 35 (-1;-2)	[0757] – 18-000457-PR03 (GAS-C01-04-en-01)		889~1200 x 2062~2942	
	4.12	Thermal transmittance	Ud to be calculated in function of the project. Pre-calculated U-values for dimensions 1230x2180mm can be found in the Uf-value tables. Uf-values are calculated under certification of BCCA: certificate BPCB-420-72-10077/2.					
	4.13	Radiation properties	These properties must be evaluated by the CE-label of the glass					
	4.14	Air permeability	3		[0960] – 21.00162 rev A		1352x2204	

Non-essential characteristics					
EN 14351-1	4.4.1	Reaction to fire	Anodized: A1 Painted: A2 Gaskets: E	EC decision 96/603/EC [1812] - EFR-21-001664A [0432] - 230006500-6	
	4.16	Operating forces	1	[0960] - 20.01458	1400x3000, 180 kg
	4.17	Mechanical strength	4	[0960] - 20.00710.1	1400x3000, 250 kg
	4.18	Ventilation	npd		
	4.19	Bullet resistance (BP version)	npd		
	4.20	Explosion resistance	npd		
	4.21	Resistance to repeated opening and closing	8 (1.000 000)	[0960] - 20.00710.1	1400x3000, 250 kg
	4.22	Behaviour between different climates	npd		
	4.23	Burglar resistance (AP version)	RC2 RC3	[1309] - 45-2/25 [1136] - EF-24-431-01	See report

De prestaties van de producten die met bovenstaande unieke identificatiecodes zijn aangeduid, zijn in overeenstemming met de betreffende opgegeven prestaties. Deze prestatieverklaring wordt afgegeven onder de uitsluitende verantwoordelijkheid van raamSELECT

Voor en namens de fabrikant ondertekend door :

Naam en functie	Plaats en datum van afgifte	Handtekening
Stijn Hoskens (directeur)	01/07/2026	

<5.5> NAAR BINNEN DRAAIENDE DEUREN MET DUBBELE VLEUGEL EN DREMPELPROFIEL



raamSELECT NV
Merksplassesteenweg 18
2310 Rijkevorsel

Aangegeven prestaties volgens
NBN EN 14351-1:2006+A2:2016




Characteristic			Performance		Notified body - Report		Tested size [mm]	
Essential characteristics								
EN 14351-1	4.2	Resistance to wind load	C2 (800 Pa) C3 (1200 Pa)		[0960] – 21.00162 rev A [0960] – 24.00680		1338x2352 533x2633	
	4.5	Watertightness	6A (250 Pa) 5A (200 Pa)		[0960] – 21.00162 rev A [0960] – 24.00680		1338x2352 533x2633	
	4.6	Dangerous substances	In the materials delivered by Reynaers, no dangerous substances as indicated in hEN 14351-1 are used.					
	4.7	Impact resistance	5 ⁽¹⁾		[0960] – SKG/HRU/age/12.0649 ⁽²⁾		649x1742	
	4.8	Load-bearing capacity of safety devices	Pass		[0960] – 22.00323		1400x3000	
	4.9	Height & width	See 6					
	4.11	Acoustic performance	Glass: 34 (-1;-4) 41 (-2;-4) 50 (-2;-8)	Doors: 36 (-3;-6) 38 (-3;-5) 41 (-1;-3)	[0757] – 18-000457-PR03 (GAS-C01-04-en-01)		889~1279 x 2062~2452	
	4.12	Thermal transmittance	Ud to be calculated in function of the project. Pre-calculated U-values for dimensions 2000x2180mm can be found in the Uf-value tables. Uf-values are calculated under certification of BCCA: certificate BPCB-420-72-10077/2.					
	4.13	Radiation properties	These properties must be evaluated by the CE-label of the glass					
	4.14	Air permeability	3 4		[0960] – 21.00162 rev A [0960] – 24.00680		1338x2352 533x2633	

Non-essential characteristics					
EN 14351-1	4.4.1	Reaction to fire	Anodized: A1 Painted: A2 Gaskets: E	EC decision 96/603/EC [1812] - EFR-21-001664A [0432] - 230006500-6	
	4.16	Operating forces	0	[0960] - 22.00323	1400x3000, 353 kg
	4.17	Mechanical strength	4	[0960] - 22.00323	1400x3000, 353 kg
	4.18	Ventilation	npd		
	4.19	Bullet resistance (BP version)	npd		
	4.20	Explosion resistance	npd		
	4.21	Resistance to repeated opening and closing	7 (500.000)	[0960] - 22.00323	1400x3000, 353 kg
	4.22	Behaviour between different climates	npd		
	4.23	Burglar resistance (AP version)	RC2 RC3	[1309] - 45-2/25 [1136] - EF-24-431-01	See report

De prestaties van de producten die met bovenstaande unieke identificatiecodes zijn aangeduid, zijn in overeenstemming met de betreffende opgegeven prestaties. Deze prestatieverklaring wordt afgegeven onder de uitsluitende verantwoordelijkheid van raamSELECT

Voor en namens de fabrikant ondertekend door :

Naam en functie	Plaats en datum van afgifte	Handtekening
Stijn Hoskens (directeur)	01/07/2026	

<5.6> NAAR BINNEN DRAAIENDE DEUREN MET DUBBELE VLEUGEL EN TOCHTRUBBER

raamSELECT

raamSELECT NV
Merksplassesteenweg 18
2310 Rijkevorsel

Aangegeven prestaties volgens
NBN EN 14351-1:2006+A2:2016




Characteristic			Performance		Notified body - Report	Tested size [mm]
Essential characteristics						
EN 14351-1	4.2	Resistance to wind load	B2 (800 Pa)		[0960] – 21.00162 rev A	1352x2500
	4.5	Watertightness	3A (100 Pa)		[0960] – 21.00162 rev A	1352x2500
	4.6	Dangerous substances	In the materials delivered by Reynaers, no dangerous substances as indicated in hEN 14351-1 are used.			
	4.7	Impact resistance	5 ⁽¹⁾		[0960] – SKG/HRU/age/12.0649 ⁽²⁾	649x1742
	4.8	Load-bearing capacity of safety devices	Pass		[0960] – 22.00323	1400x3000
	4.9	Height & width	See 6			
	4.11	Acoustic performance	Glass: 34 (-1;-4) 41 (-2;-4) 50 (-2;-8)	Doors: 33 (-2;-5) 34 (-1;-3) 35 (-1;-2)	[0757] – 18-000457-PR03 (GAS-C01-04-en-01)	889~1200 x 2062~2452
	4.12	Thermal transmittance	Ud to be calculated in function of the project. Pre-calculated U-values for dimensions 2000x2180mm can be found in the Uf-value tables. Uf-values are calculated under certification of BCCA: certificate BPCB-420-72-10077/2.			
	4.13	Radiation properties	These properties must be evaluated by the CE-label of the glass			
	4.14	Air permeability	2		[0960] – 21.00162 rev A	1352x2500

Non-essential characteristics					
EN 14351-1	4.4.1	Reaction to fire	Anodized: A1 Painted: A2 Gaskets: E	EC decision 96/603/EC [1812] - EFR-21-001664A [0432] - 230006500-6	
	4.16	Operating forces	0	[0960] - 22.00323	1400x3000, 353 kg
	4.17	Mechanical strength	4	[0960] - 22.00323	1400x3000, 353 kg
	4.18	Ventilation	npd		
	4.19	Bullet resistance (BP version)	npd		
	4.20	Explosion resistance	npd		
	4.21	Resistance to repeated opening and closing	7 (500.000)	[0960] - 22.00323	1400x3000, 353 kg
	4.22	Behaviour between different climates	npd		
	4.23	Burglar resistance (AP version)	RC2 RC3	[1309] - 45-2/25 [1136] - EF-24-431-01	See report

De prestaties van de producten die met bovenstaande unieke identificatiecodes zijn aangeduid, zijn in overeenstemming met de betreffende opgegeven prestaties. Deze prestatieverklaring wordt afgegeven onder de uitsluitende verantwoordelijkheid van raamSELECT

Voor en namens de fabrikant ondertekend door :

Naam en functie	Plaats en datum van afgifte	Handtekening
Stijn Hoskens (directeur)	01/07/2026	

<5.7> NAAR BUITEN DRAAIENDE DEUREN MET DUBBELE VLEUGEL EN DREMPELPROFIEL



raamSELECT NV
Merksplassesteenweg 18
2310 Rijkevorsel

Aangegeven prestaties volgens
NBN EN 14351-1:2006+A2:2016




Characteristic			Performance		Notified body - Report		Tested size [mm]	
Essential characteristics								
EN 14351-1	4.2	Resistance to wind load	C2 (800 Pa)		[0960] – 21.00162 rev A		1339x2352	
	4.5	Watertightness	7A (300 Pa)		[0960] – 21.00162 rev A		1339x2352	
	4.6	Dangerous substances	In the materials delivered by Reynaers, no dangerous substances as indicated in hEN 14351-1 are used.					
	4.7	Impact resistance	5 ⁽¹⁾		[0960] – SKG/HRU/age/12.0649 ⁽²⁾		649x1742	
	4.8	Load-bearing capacity of safety devices	Pass		[0960] – 22.00323		1400x3000	
	4.9	Height & width	See 6					
	4.11	Acoustic performance	Glass: 34 (-1;-4) 41 (-2;-4) 50 (-2;-8)	Doors: 36 (-3;-6) 38 (-3;-5) 41 (-1;-3)	[0757] – 18-000457-PR03 (GAS-C01-04-en-01)		889~1279 x 2062~2452	
	4.12	Thermal transmittance	Ud to be calculated in function of the project. Pre-calculated U-values for dimensions 2000x2180mm can be found in the Uf-value tables. Uf-values are calculated under certification of BCCA: certificate BPCB-420-72-10077/2.					
	4.13	Radiation properties	These properties must be evaluated by the CE-label of the glass					
	4.14	Air permeability	3		[0960] – 21.00162 rev A		1339x2352	

Non-essential characteristics					
EN 14351-1	4.4.1	Reaction to fire	Anodized: A1 Painted: A2 Gaskets: E	EC decision 96/603/EC [1812] - EFR-21-001664A [0432] – 230006500-6	
	4.16	Operating forces	0	[0960] – 22.00323	1400x3000, 353 kg
	4.17	Mechanical strength	4	[0960] – 22.00323	1400x3000, 353 kg
	4.18	Ventilation	npd		
	4.19	Bullet resistance (BP version)	npd		
	4.20	Explosion resistance	npd		
	4.21	Resistance to repeated opening and closing	7 (500.000)	[0960] – 22.00323	1400x3000, 353 kg
	4.22	Behaviour between different climates	npd		
	4.23	Burglar resistance (AP version)	RC2 RC3	[1309] – 45-2/25 [1136] – EF-24-431-01	See report

De prestaties van de producten die met bovenstaande unieke identificatiecodes zijn aangeduid, zijn in overeenstemming met de betreffende opgegeven prestaties. Deze prestatieverklaring wordt afgegeven onder de uitsluitende verantwoordelijkheid van raamSELECT

Voor en namens de fabrikant ondertekend door :

Naam en functie	Plaats en datum van afgifte	Handtekening
Stijn Hoskens (directeur)	01/07/2026	

<5.8> NAAR BUITEN DRAAIENDE DEUREN MET DUBBELE VLEUGEL EN TOCHTRUBBER



raamSELECT NV
Merksplassesteenweg 18
2310 Rijkevorsel

Aangegeven prestaties volgens
NBN EN 14351-1:2006+A2:2016




Characteristic			Performance		Notified body - Report		Tested size [mm]	
Essential characteristics								
EN 14351-1	4.2	Resistance to wind load	C2 (800 Pa)		[0960] – 21.00162 rev A		1352x2500	
	4.5	Watertightness	3A (100 Pa)		[0960] – 21.00162 rev A		1352x2500	
	4.6	Dangerous substances	In the materials delivered by Reynaers, no dangerous substances as indicated in hEN 14351-1 are used.					
	4.7	Impact resistance	5 ⁽¹⁾		[0960] – SKG/HRU/age/12.0649 ⁽²⁾		649x1742	
	4.8	Load-bearing capacity of safety devices	Pass		[0960] – 22.00323		1400x3000	
	4.9	Height & width	See 6					
	4.11	Acoustic performance	Glass: 34 (-1;-4) 41 (-2;-4) 50 (-2;-8)		Doors: 33 (-2;-5) 34 (-1;-3) 35 (-1;-2)		[0757] – 18-000457-PR03 (GAS-C01-04-en-01) 889~1200 x 2062~2452	
	4.12	Thermal transmittance	Ud to be calculated in function of the project. Pre-calculated U-values for dimensions 2000x2180mm can be found in the Uf-value tables. Uf-values are calculated under certification of BCCA: certificate BPCB-420-72-10077/2.					
	4.13	Radiation properties	These properties must be evaluated by the CE-label of the glass					
	4.14	Air permeability	2		[0960] – 21.00162 rev A		1352x2500	

Non-essential characteristics					
EN 14351-1	4.4.1	Reaction to fire	Anodized: A1 Painted: A2 Gaskets: E	EC decision 96/603/EC [1812] - EFR-21-001664A [0432] – 230006500-6	
	4.16	Operating forces	0	[0960] – 22.00323	1400x3000, 353 kg
	4.17	Mechanical strength	4	[0960] – 22.00323	1400x3000, 353 kg
	4.18	Ventilation	npd		
	4.19	Bullet resistance (BP version)	npd		
	4.20	Explosion resistance	npd		
	4.21	Resistance to repeated opening and closing	7 (500.000)	[0960] – 22.00323	1400x3000, 353 kg
	4.22	Behaviour between different climates	npd		
	4.23	Burglar resistance (AP version)	RC2 RC3	[1309] – 45-2/25 [1136] – EF-24-431-01	See report

De prestaties van de producten die met bovenstaande unieke identificatiecodes zijn aangeduid, zijn in overeenstemming met de betreffende opgegeven prestaties. Deze prestatieverklaring wordt afgegeven onder de uitsluitende verantwoordelijkheid van raamSELECT

Voor en namens de fabrikant ondertekend door :


Naam en functie	Plaats en datum van afgifte	Handtekening
Stijn Hoskens (directeur)	01/07/2026	

<5.9> PIVOTERENDE DEUREN



raamSELECT NV
Merksplassesteenweg 18
2310 Rijkevorsel

Aangegeven prestaties volgens
NBN EN 14351-1:2006+A2:2016




Characteristic			Performance	Notified body - Report	Tested size [mm]
Essential characteristics					
EN 14351-1	4.2	Resistance to wind load	C3 (1200 Pa)	[0960] – 19.00305 ⁽⁵⁾	1700x2700
	4.5	Watertightness	4A (150 Pa)	[0960] – 19.00305 ⁽⁵⁾	1700x2700
	4.6	Dangerous substances	In the materials delivered by Reynaers, no dangerous substances as indicated in hEN 14351-1 are used.		
	4.7	Impact resistance	npd		
	4.8	Load-bearing capacity of safety devices	Pass	[0960] – 18.01316	1700x2700
	4.9	Height & width	See 6		
	4.11	Acoustic performance	npd		
	4.12	Thermal transmittance	Ud to be calculated in function of the project. Pre-calculated U-values for dimensions 1230x2180mm can be found in the Uf-value tables. Uf-values are calculated under certification of BCCA: certificate BPCB-420-72-10077/2.		
	4.13	Radiation properties	These properties must be evaluated by the CE-label of the glass		
	4.14	Air permeability	4	[0960] – 19.00305 ⁽⁵⁾	1700x2700

Non-essential characteristics					
EN 14351-1	4.4.1	Reaction to fire	Anodized: A1 Painted: A2 Gaskets: E	EC decision 96/603/EC [1812] - EFR-21-001664A [0432] – 230006500-6	
	4.16	Operating forces	1	[0960] – 18.01316	1700x2700, 204 kg
	4.17	Mechanical strength	4	[0960] – 18.01316	1700x2700, 204 kg
	4.18	Ventilation	npd		
	4.19	Bullet resistance (BP version)	npd		
	4.20	Explosion resistance	npd		
	4.21	Resistance to repeated opening and closing	5 (100 000)	[0960] – 18.01316	1700x2700, 204 kg
	4.22	Behaviour between different climates	npd		
	4.23	Burglar resistance (AP version)	RC2 ⁽⁵⁾	[1136] – CAR-19-075 [1136] – CAR-19-257	See report

De prestaties van de producten die met bovenstaande unieke identificatiecodes zijn aangeduid, zijn in overeenstemming met de betreffende opgegeven prestaties. Deze prestatieverklaring wordt afgegeven onder de uitsluitende verantwoordelijkheid van raamSELECT

Voor en namens de fabrikant ondertekend door :


Naam en functie	Plaats en datum van afgifte	Handtekening
Stijn Hoskens (directeur)	01/07/2026	

<5.10> PIVOTERENDE DEUREN XL



raamSELECT NV
Merksplassesteenweg 18
2310 Rijkevorsel

Aangegeven prestaties volgens
NBN EN 14351-1:2006+A2:2016



Characteristic			Performance	Notified body - Report	Tested size [mm]
Essential characteristics					
EN 14351-1	4.2	Resistance to wind load	C2 (800 Pa)	[0960] – 25.01497 Rev A	2500 x 4000
	4.5	Watertightness	6A (250 Pa)	[0960] – 25.01497 Rev A	2500 x 4000
	4.6	Dangerous substances	In the materials delivered by Reynaers, no dangerous substances as indicated in hEN 14351-1 are used.		
	4.7	Impact resistance	npd		
	4.8	Load-bearing capacity of safety devices	Pass	[0960] – 21.00298	2500 x 3559
	4.9	Height & width	See 6		
	4.11	Acoustic performance	npd		
	4.12	Thermal transmittance	Ud to be calculated in function of the project. Pre-calculated U-values for dimensions 1230x2180mm can be found in the Uf-value tables. Uf-values are calculated under certification of BCCA: certificate BPCB-420-72-10077/2.		
	4.13	Radiation properties	These properties must be evaluated by the CE-label of the glass		
	4.14	Air permeability	3	[0960] – 25.01497 Rev A	2500 x 4000

Non-essential characteristics					
EN 14351-1	4.4.1	Reaction to fire	Anodized: A1 Painted: A2 Gaskets: E	EC decision 96/603/EC [1812] - EFR-21-001664A [0432] – 230006500-6	
	4.16	Operating forces	3	[0960] – 25.01228	2500 x 3800, 485 kg
	4.17	Mechanical strength	4	[0960] – 21.00298	2500x3559, 488 kg
	4.18	Ventilation	npd		
	4.19	Bullet resistance (BP version)	npd		
	4.20	Explosion resistance	npd		
	4.21	Resistance to repeated opening and closing	5 (100 000)	[0960] – 25.01228	2500 x 3800, 485 kg
	4.22	Behaviour between different climates	npd		
	4.23	Burglar resistance (AP version)	npd		

De prestaties van de producten die met bovenstaande unieke identificatiecodes zijn aangeduid, zijn in overeenstemming met de betreffende opgegeven prestaties. Deze prestatieverklaring wordt afgegeven onder de uitsluitende verantwoordelijkheid van raamSELECT

Voor en namens de fabrikant ondertekend door :

Naam en functie	Plaats en datum van afgifte	Handtekening
Stijn Hoskens (directeur)	01/07/2026	