




PRESTATIEVERKLARING

REYNAERS DEUREN – SL38

Nr. R-04

d.d. 01/07/2026

Productnaam	Deuren vervaardigd uit de profielsystemen : Reynaers SL38			
Type aanduiding	<5.1> Naar binnen draaiende deuren met enkele vleugel en drempelprofiel <5.2> Naar binnen draaiende deuren met enkele vleugel en tochttribber <5.3> Naar buiten draaiende deuren met enkele vleugel en drempelprofiel <5.4> Naar buiten draaiende deuren met enkele vleugel en tochttribber <5.5> Naar binnen draaiende deuren met dubbele vleugel en drempelprofiel <5.6> Naar binnen draaiende deuren met dubbele vleugel en tochttribber <5.7> Naar buiten draaiende deuren met dubbele vleugel en drempelprofiel <5.8> Naar buiten draaiende deuren met dubbele vleugel en tochttribber			
Toepassing	Reynaers deuren SL38 voor toepassing in woningen en utiliteitsgebouwen zonder brand- en rookwerende eigenschappen.			
Naam en contactadres fabrikant	raamSELECT NV Merksplassesteenweg 18 2310 Rijkevorsel			
Naam en contactadres gemachtigde	Niet van toepassing			
Systeem voor de beoordeling en verificatie van de prestatiebestendigheid	AVCP 3			
Activiteit van de aangemelde certificatie-instantie volgens NBN EN 14351-1:2006+A2:2016	ID	Name	Address	Country
	0074	CENTRE D'EXPERTISE DU BÂTIMENT ET DES TRAVAUX PUBLICS	Domaine De Saint-Paul – 102, Route de Limours 78471 Saint-Remy-Les-Chevreuse Cedex	France
	0336	TÜV RHEINLAND NEDERLAND	Westervoortsedijk 73 6827 AV Arnhem	Netherlands
	0432	MATERIALPRÜFUNGSAMT NORDRHEIN-WESTFALEN	Auf den Thronen 2 59597 Erwitte	Germany
	0679	CENTRE SCIENTIFIQUE ET TECHNIQUE DU BÂTIMENT	84, Avenue Jean Jaurès Champs-sur-Marne F-77447 Marne-la-Vallée Cedex 2	France
	0744	SOCOTEC	Les Quadrants – 3,Avenue du Centre – Guyancourt 78182 St-Quentin en Yvelines	France
	0749	BELGIAN CONSTRUCTION CERTIFICATION ASSOCIATION	Aarlenstraat 53 1040 Brussel	Belgium
	0757	IFT ROSENHEIM	Theodor-Gietl-Strasse 7-9 83026 Rosenheim	Germany
	0845	DANISH INSTITUTE OF FIRE AND SECURITY TECHNOLOGY	Jernholmen, 12 2650 Hvidovre	Denmark
	0960	SKG-IKOB	Poppenbouwing 56 4191 NZ Geldermalsen	Netherlands
	1136	BELGIAN BUILDING RESEARCH INSITUTE	Lombardstraat 42 1000 Brussel	Belgium
	1234	EFFECTIS NEDERLAND	Brandpuntlaan Zuid 16, Postbus 554 2665 ZN Bleiswijk	Netherlands
	1288	WINTech ENGINEERING LIMITED	Halesfield 2 Telford, Shropshire TF7 4QH	United Kingdom
	1309	PRÜFINSTITUT SCHLÖSSER UND BESCHLÄGE, VELBERT	Wallstrasse 41 42551 Velbert	Germany
	1488	INSTYTUT TECHNIKI BUDOWLANEJ	ul. Filtrawa 1 00-611 Warszawa	Poland
	1671	PEUTZ	Lindenlaan 41, Molenhoek PO Box 66 6585 ZH MOOK	Netherlands
	1749	TNO DEFENCE, SECURITY AND SAFETY	Lange Kleiweg 137, Postbus 45 2280 AA Rijswijk	Netherlands
	1769	UNIVERSITY OF GENT	Sint-Pietersnieuwstraat 41 9000 Gent	Belgium
	1812	EFFECTIS FRANCE	ZI. Les Nappes 149, route du Marc 38630 Les Aveniers Veyrins-Thuellin	France
	2211	INSTITUTO DE INVESTIGAÇÃO E DESENVOLVIMENTO TECNOLÓGICO PARA A CONSTRUÇÃO, ENERGIA, AMBIENTE E SUSTENTABILIDADE	Rua Pedro Hispano Pólo II da Universidade de Coimbra 3030-289 Coimbra	Portugal
	2434	CENTRUM TECHNIKI OKRĘTOWEJ	ul. Szczecińska 65 80-392 Gdańsk	Poland
	2509	DMT	Hermann-Kemper-Str. 12a	Germany

Namens het management van	Datum	Naam	Handtekening
raamSELECT NV	01/07/2026	Stijn Hoskens	

<5.1> NAAR BINNEN DRAAIENDE DEUREN MET ENKELE VLEUGEL EN DREMPELPROFIEL



raamSELECT NV
Merksplassesteenweg 18
2310 Rijkevorsel

Aangegeven prestaties volgens
NBN EN 14351-1:2006+A2:2016




Characteristic			Performance		Notified body - Report	Tested size [mm]
Essential characteristics						
EN 14351-1	4.2	Resistance to wind load	C3 (1200 Pa)		[0960] – 24.01560 ^[B]	1100 x 2250
	4.5	Watertightness	8A (450 Pa) E900 (900 Pa) **		[0960] – 24.01560 ^[B]	1100 x 2250
	4.6	Dangerous substances	In the materials delivered by Reynaers, no dangerous substances as indicated in hEN 14351-1 are used.			
	4.7	Impact resistance	5 (950 mm)		[0960] – 09.1169 *	642 x 1758
	4.8	Load-bearing capacity of safety devices	npd			
	4.9	Height & width	See 6			
	4.11	Acoustic performance	Glass: 36 (-1;-5) 41 (-2;-4) 45 (-2;-6) 50 (-2;-8)	Doors: 36 (-1;-5) 38 (-1;-3) 41 (-2;-4) 42 (-1;-3)	[0960] – 25.00720	1350 x 2350
	4.12	Thermal transmittance	Ud to be calculated in function of the project. Pre-calculated U-values for dimensions 1230x2180mm can be found in the Uf-value tables. Uf-values are calculated under certification of BCCA: certificate BPCB-420-72-10077/2.			
	4.13	Radiation properties	These properties must be evaluated by the CE-label of the glass			
	4.14	Air permeability	4		[0960] – 24.01560 ^[B]	1100 x 2250

Non-essential characteristics					
EN 14351-1	4.4.1	Reaction to fire	Anodized: A1 Painted: A2 Gaskets: E	EC decision 96/603/EC [1812] - EFR-21-001664A [0432] – 230006500-6	
	4.16	Operating forces	2 1	[0960] – 22.00087.2 ^[A] [0960] – 24.00379 ^[B]	1100x2400, 179 kg 1168x2763, 131 kg
	4.17	Mechanical strength	3	[0960] – 24.00379.1 ^[B]	1168x2763, 131 kg
	4.18	Ventilation	npd		
	4.19	Bullet resistance (BP version)	npd		
	4.20	Explosion resistance	npd		
	4.21	Resistance to repeated opening and closing	6 (200.000) 4 (50.000)	[0960] – 22.00087.2 ^[A] [0960] – 24.00379 ^[B]	1100x2400, 179 kg 1168x2763, 131 kg
	4.22	Behaviour between different climates	npd		
	4.23	Burglar resistance (AP version)	RC2	[0960] – SKG.0837.0232 ^[A]	See report

De prestaties van de producten die met bovenstaande unieke identificatiecodes zijn aangeduid, zijn in overeenstemming met de betreffende opgegeven prestaties. Deze prestatieverklaring wordt afgegeven onder de uitsluitende verantwoordelijkheid van raamSELECT

Voor en namens de fabrikant ondertekend door :

Naam en functie	Plaats en datum van afgifte	Handtekening
Stijn Hoskens (directeur)	01/07/2026	

<5.2> NAAR BINNEN DRAAIENDE DEUREN MET ENKELE VLEUGEL EN TOCHTRUBBER



raamSELECT NV
Merksplassesteenweg 18
2310 Rijkevorsel

Aangegeven prestaties volgens
NBN EN 14351-1:2006+A2:2016




Characteristic			Performance	Notified body - Report	Tested size [mm]
Essential characteristics					
EN 14351-1	4.2	Resistance to wind load	npd		
	4.5	Watertightness	npd		
	4.6	Dangerous substances	In the materials delivered by Reynaers, no dangerous substances as indicated in hEN 14351-1 are used.		
	4.7	Impact resistance	5 (950 mm)	[0960] – 09.1169 *	642 x 1758
	4.8	Load-bearing capacity of safety devices	npd		
	4.9	Height & width	See 6		
	4.11	Acoustic performance	npd		
	4.12	Thermal transmittance	Ud to be calculated in function of the project. Pre-calculated U-values for dimensions 1230x2180mm can be found in the Uf-value tables. Uf-values are calculated under certification of BCCA: certificate BPCB-420-72-10077/2.		
	4.13	Radiation properties	These properties must be evaluated by the CE-label of the glass		
	4.14	Air permeability	npd		

Non-essential characteristics					
EN 14351-1	4.4.1	Reaction to fire	Anodized: A1 Painted: A2 Gaskets: E	EC decision 96/603/EC [1812] - EFR-21-001664A [0432] – 230006500-6	
	4.16	Operating forces	2 1	[0960] – 22.00087.2 ^[A] [0960] – 24.00379 ^[B]	1100x2400, 179 kg 1168x2763, 131 kg
	4.17	Mechanical strength	3	[0960] – 24.00379.1 ^[B]	1168x2763, 131 kg
	4.18	Ventilation	npd		
	4.19	Bullet resistance (BP version)	npd		
	4.20	Explosion resistance	npd		
	4.21	Resistance to repeated opening and closing	6 (200.000) 4 (50.000)	[0960] – 22.00087.2 ^[A] [0960] – 24.00379 ^[B]	1100x2400, 179 kg 1168x2763, 131 kg
	4.22	Behaviour between different climates	npd		
	4.23	Burglar resistance (AP version)	RC2	[0960] – SKG.0837.0232 ^[A]	See report

De prestaties van de producten die met bovenstaande unieke identificatiecodes zijn aangeduid, zijn in overeenstemming met de betreffende opgegeven prestaties. Deze prestatieverklaring wordt afgegeven onder de uitsluitende verantwoordelijkheid van raamSELECT

Voor en namens de fabrikant ondertekend door :

Naam en functie	Plaats en datum van afgifte	Handtekening
Stijn Hoskens (directeur)	01/07/2026	

<5.3> NAAR BUITEN DRAAIENDE DEUREN MET ENKELE VLEUGEL EN DREMPELPROFIEL



raamSELECT NV
Merksplassesteenweg 18
2310 Rijkevorsel

Aangegeven prestaties volgens
NBN EN 14351-1:2006+A2:2016




Characteristic			Performance		Notified body - Report	Tested size [mm]
Essential characteristics						
EN 14351-1	4.2	Resistance to wind load	C3 (1200 Pa)		[0960] – 25.00897 ^[A] [0960] – 24.01560 ^[B]	888 x 2363 1012 x 2357
	4.5	Watertightness	9A (600 Pa)		[0960] – 25.00897 ^[A] [0960] – 24.01560 ^[B]	888 x 2363 1012 x 2357
	4.6	Dangerous substances	In the materials delivered by Reynaers, no dangerous substances as indicated in hEN 14351-1 are used.			
	4.7	Impact resistance	5 (950 mm)		[0960] – 09.1169 *	642 x 1758
	4.8	Load-bearing capacity of safety devices	npd			
	4.9	Height & width	See 6			
	4.11	Acoustic performance	Glass: 36 (-1;-5) 41 (-2;-4) 45 (-2;-6) 50 (-2;-8)	Doors: 36 (-1;-5) 38 (-1;-3) 41 (-2;-4) 42 (-1;-3)	[0960] – 25.00720	1350 x 2350
	4.12	Thermal transmittance	Ud to be calculated in function of the project. Pre-calculated U-values for dimensions 1230x2180mm can be found in the Uf-value tables. Uf-values are calculated under certification of BCCA: certificate BPCB-420-72-10077/2.			
	4.13	Radiation properties	These properties must be evaluated by the CE-label of the glass			
	4.14	Air permeability	4		[0960] – 25.00897 ^[A] [0960] – 24.01560 ^[B]	888 x 2363 1012 x 2357

Non-essential characteristics					
EN 14351-1	4.4.1	Reaction to fire	Anodized: A1 Painted: A2 Gaskets: E	EC decision 96/603/EC [1812] - EFR-21-001664A [0432] – 230006500-6	
	4.16	Operating forces	2 1	[0960] – 22.00087.2 ^[A] [0960] – 24.00379 ^[B]	1100x2400, 179 kg 1168x2763, 131 kg
	4.17	Mechanical strength	3	[0960] – 24.00379.1 ^[B]	1168x2763, 131 kg
	4.18	Ventilation	npd		
	4.19	Bullet resistance (BP version)	npd		
	4.20	Explosion resistance	npd		
	4.21	Resistance to repeated opening and closing	6 (200.000) 4 (50.000)	[0960] – 22.00087.2 ^[A] [0960] – 24.00379 ^[B]	1100x2400, 179 kg 1168x2763, 131 kg
	4.22	Behaviour between different climates	npd		
	4.23	Burglar resistance (AP version)	RC2	[0960] – SKG.0837.0232 ^[A]	See report

De prestaties van de producten die met bovenstaande unieke identificatiecodes zijn aangeduid, zijn in overeenstemming met de betreffende opgegeven prestaties. Deze prestatieverklaring wordt afgegeven onder de uitsluitende verantwoordelijkheid van raamSELECT

Voor en namens de fabrikant ondertekend door :


Naam en functie	Plaats en datum van afgifte	Handtekening
Stijn Hoskens (directeur)	01/07/2026	

<5.4> NAAR BUITEN DRAAIENDE DEUREN MET ENKELE VLEUGEL EN TOCHTRUBBER



raamSELECT NV
Merksplassesteenweg 18
2310 Rijkevorsel

Aangegeven prestaties volgens
NBN EN 14351-1:2006+A2:2016




Characteristic			Performance	Notified body - Report	Tested size [mm]
Essential characteristics					
EN 14351-1	4.2	Resistance to wind load	C3 (1200 Pa)	[0960] – 25.00897 ^[A]	888 x 2363
	4.5	Watertightness	npd		
	4.6	Dangerous substances	In the materials delivered by Reynaers, no dangerous substances as indicated in hEN 14351-1 are used.		
	4.7	Impact resistance	5 (950 mm)	[0960] – 09.1169 *	642 x 1758
	4.8	Load-bearing capacity of safety devices	npd		
	4.9	Height & width	See 6		
	4.11	Acoustic performance	npd		
	4.12	Thermal transmittance	Ud to be calculated in function of the project. Pre-calculated U-values for dimensions 1230x2180mm can be found in the Uf-value tables. Uf-values are calculated under certification of BCCA: certificate BPCB-420-72-10077/2.		
	4.13	Radiation properties	These properties must be evaluated by the CE-label of the glass		
	4.14	Air permeability	npd		

Non-essential characteristics					
EN 14351-1	4.4.1	Reaction to fire	Anodized: A1 Painted: A2 Gaskets: E	EC decision 96/603/EC [1812] - EFR-21-001664A [0432] – 230006500-6	
	4.16	Operating forces	2 1	[0960] – 22.00087.2 ^[A] [0960] – 24.00379 ^[B]	1100x2400, 179 kg 1168x2763, 131 kg
	4.17	Mechanical strength	3	[0960] – 24.00379.1 ^[B]	1168x2763, 131 kg
	4.18	Ventilation	npd		
	4.19	Bullet resistance (BP version)	npd		
	4.20	Explosion resistance	npd		
	4.21	Resistance to repeated opening and closing	6 (200.000) 4 (50.000)	[0960] – 22.00087.2 ^[A] [0960] – 24.00379 ^[B]	1100x2400, 179 kg 1168x2763, 131 kg
	4.22	Behaviour between different climates	npd		
	4.23	Burglar resistance (AP version)	RC2	[0960] – SKG.0837.0232 ^[A]	See report

De prestaties van de producten die met bovenstaande unieke identificatiecodes zijn aangeduid, zijn in overeenstemming met de betreffende opgegeven prestaties. Deze prestatieverklaring wordt afgegeven onder de uitsluitende verantwoordelijkheid van raamSELECT

Voor en namens de fabrikant ondertekend door :


Naam en functie	Plaats en datum van afgifte	Handtekening
Stijn Hoskens (directeur)	01/07/2026	

<5.5> NAAR BINNEN DRAAIENDE DEUREN MET DUBBELE VLEUGEL EN DREMPELPROFIEL



raamSELECT NV
Merksplassesteenweg 18
2310 Rijkevorsel

Aangegeven prestaties volgens
NBN EN 14351-1:2006+A2:2016




Characteristic			Performance		Notified body - Report		Tested size [mm]	
Essential characteristics								
EN 14351-1	4.2	Resistance to wind load	C3 (1200 Pa)		[0960] – 24.01560 ^[B]		1100 x 2250	
	4.5	Watertightness	8A (450 Pa) E900 (900 Pa) **		[0960] – 24.01560 ^[B]		1100 x 2250	
	4.6	Dangerous substances	In the materials delivered by Reynaers, no dangerous substances as indicated in hEN 14351-1 are used.					
	4.7	Impact resistance	5 (950 mm)		[0960] – 09.1169 *		642 x 1758	
	4.8	Load-bearing capacity of safety devices	npd					
	4.9	Height & width	See 6					
	4.11	Acoustic performance	Glass: 36 (-1;-5) 41 (-2;-4) 45 (-2;-6) 50 (-2;-8)	Doors: 36 (-1;-5) 38 (-1;-3) 41 (-2;-4) 42 (-1;-3)	[0960] – 25.00720		1350 x 2350	
	4.12	Thermal transmittance	Ud to be calculated in function of the project. Pre-calculated U-values for dimensions 2000x2180mm can be found in the Uf-value tables. Uf-values are calculated under certification of BCCA: certificate BPCB-420-72-10077/2.					
	4.13	Radiation properties	These properties must be evaluated by the CE-label of the glass					
	4.14	Air permeability	4		[0960] – 24.01560 ^[B]		1100 x 2250	

Non-essential characteristics					
EN 14351-1	4.4.1	Reaction to fire	Anodized: A1 Painted: A2 Gaskets: E	EC decision 96/603/EC [1812] - EFR-21-001664A [0432] – 230006500-6	
	4.16	Operating forces	2 1	[0960] – 22.00087.2 ^[A] [0960] – 24.00379 ^[B]	1100x2400, 179 kg 1168x2763, 131 kg
	4.17	Mechanical strength	3	[0960] – 24.00379.1 ^[B]	1168x2763, 131 kg
	4.18	Ventilation	npd		
	4.19	Bullet resistance (BP version)	npd		
	4.20	Explosion resistance	npd		
	4.21	Resistance to repeated opening and closing	6 (200.000) 4 (50.000)	[0960] – 22.00087.2 ^[A] [0960] – 24.00379 ^[B]	1100x2400, 179 kg 1168x2763, 131 kg
	4.22	Behaviour between different climates	npd		
	4.23	Burglar resistance (AP version)	RC2	[0960] – SKG.0837.0232 ^[A]	See report

De prestaties van de producten die met bovenstaande unieke identificatiecodes zijn aangeduid, zijn in overeenstemming met de betreffende opgegeven prestaties. Deze prestatieverklaring wordt afgegeven onder de uitsluitende verantwoordelijkheid van raamSELECT

Voor en namens de fabrikant ondertekend door :

Naam en functie	Plaats en datum van afgifte	Handtekening
Stijn Hoskens (directeur)	01/07/2026	

<5.6> NAAR BINNEN DRAAIENDE DEUREN MET DUBBELE VLEUGEL EN TOCHTRUBBER



raamSELECT NV
Merksplassesteenweg 18
2310 Rijkevorsel

Aangegeven prestaties volgens
NBN EN 14351-1:2006+A2:2016




Characteristic			Performance	Notified body - Report	Tested size [mm]
Essential characteristics					
EN 14351-1	4.2	Resistance to wind load	npd		
	4.5	Watertightness	npd		
	4.6	Dangerous substances	In the materials delivered by Reynaers, no dangerous substances as indicated in hEN 14351-1 are used.		
	4.7	Impact resistance	5 (950 mm)	[0960] – 09.1169 *	642 x 1758
	4.8	Load-bearing capacity of safety devices	npd		
	4.9	Height & width	See 6		
	4.11	Acoustic performance	npd		
	4.12	Thermal transmittance	Ud to be calculated in function of the project. Pre-calculated U-values for dimensions 2000x2180mm can be found in the Uf-value tables. Uf-values are calculated under certification of BCCA: certificate BPCB-420-72-10077/2.		
	4.13	Radiation properties	These properties must be evaluated by the CE-label of the glass		
	4.14	Air permeability	npd		

Non-essential characteristics					
EN 14351-1	4.4.1	Reaction to fire	Anodized: A1 Painted: A2 Gaskets: E	EC decision 96/603/EC [1812] - EFR-21-001664A [0432] – 230006500-6	
	4.16	Operating forces	2 1	[0960] – 22.00087.2 ^[A] [0960] – 24.00379 ^[B]	1100x2400, 179 kg 1168x2763, 131 kg
	4.17	Mechanical strength	3	[0960] – 24.00379.1 ^[B]	1168x2763, 131 kg
	4.18	Ventilation	npd		
	4.19	Bullet resistance (BP version)	npd		
	4.20	Explosion resistance	npd		
	4.21	Resistance to repeated opening and closing	6 (200.000) 4 (50.000)	[0960] – 22.00087.2 ^[A] [0960] – 24.00379 ^[B]	1100x2400, 179 kg 1168x2763, 131 kg
	4.22	Behaviour between different climates	npd		
	4.23	Burglar resistance (AP version)	RC2	[0960] – SKG.0837.0232 ^[A]	See report

De prestaties van de producten die met bovenstaande unieke identificatiecodes zijn aangeduid, zijn in overeenstemming met de betreffende opgegeven prestaties. Deze prestatieverklaring wordt afgegeven onder de uitsluitende verantwoordelijkheid van raamSELECT

Voor en namens de fabrikant ondertekend door :

Naam en functie	Plaats en datum van afgifte	Handtekening
Stijn Hoskens (directeur)	01/07/2026	

<5.7> NAAR BUITEN DRAAIENDE DEUREN MET DUBBELE VLEUGEL EN DREMPELPROFIEL



raamSELECT NV
Merksplassesteenweg 18
2310 Rijkevorsel

Aangegeven prestaties volgens
NBN EN 14351-1:2006+A2:2016




Characteristic			Performance		Notified body - Report	Tested size [mm]
Essential characteristics						
EN 14351-1	4.2	Resistance to wind load	C3 (1200 Pa)		[0960] – 25.00897 ^[A] [0960] – 24.01560 ^[B]	888 x 2363 1012 x 2357
	4.5	Watertightness	9A (600 Pa)		[0960] – 25.00897 ^[A] [0960] – 24.01560 ^[B]	888 x 2363 1012 x 2357
	4.6	Dangerous substances	In the materials delivered by Reynaers, no dangerous substances as indicated in hEN 14351-1 are used.			
	4.7	Impact resistance	5 (950 mm)		[0960] – 09.1169 *	642 x 1758
	4.8	Load-bearing capacity of safety devices	npd			
	4.9	Height & width	See 6			
	4.11	Acoustic performance	Glass: 36 (-1;-5) 41 (-2;-4) 45 (-2;-6) 50 (-2;-8)	Doors: 36 (-1;-5) 38 (-1;-3) 41 (-2;-4) 42 (-1;-3)	[0960] – 25.00720	1350 x 2350
	4.12	Thermal transmittance	Ud to be calculated in function of the project. Pre-calculated U-values for dimensions 2000x2180mm can be found in the Uf-value tables. Uf-values are calculated under certification of BCCA: certificate BPCB-420-72-10077/2.			
	4.13	Radiation properties	These properties must be evaluated by the CE-label of the glass			
	4.14	Air permeability	4		[0960] – 25.00897 ^[A] [0960] – 24.01560 ^[B]	888 x 2363 1012 x 2357

Non-essential characteristics					
EN 14351-1	4.4.1	Reaction to fire	Anodized: A1 Painted: A2 Gaskets: E	EC decision 96/603/EC [1812] - EFR-21-001664A [0432] – 230006500-6	
	4.16	Operating forces	2 1	[0960] – 22.00087.2 ^[A] [0960] – 24.00379 ^[B]	1100x2400, 179 kg 1168x2763, 131 kg
	4.17	Mechanical strength	3	[0960] – 24.00379.1 ^[B]	1168x2763, 131 kg
	4.18	Ventilation	npd		
	4.19	Bullet resistance (BP version)	npd		
	4.20	Explosion resistance	npd		
	4.21	Resistance to repeated opening and closing	6 (200.000) 4 (50.000)	[0960] – 22.00087.2 ^[A] [0960] – 24.00379 ^[B]	1100x2400, 179 kg 1168x2763, 131 kg
	4.22	Behaviour between different climates	npd		
	4.23	Burglar resistance (AP version)	RC2	[0960] – SKG.0837.0232 ^[A]	See report

De prestaties van de producten die met bovenstaande unieke identificatiecodes zijn aangeduid, zijn in overeenstemming met de betreffende opgegeven prestaties. Deze prestatieverklaring wordt afgegeven onder de uitsluitende verantwoordelijkheid van raamSELECT

Voor en namens de fabrikant ondertekend door :

Naam en functie	Plaats en datum van afgifte	Handtekening
Stijn Hoskens (directeur)	01/07/2026	

<5.8> NAAR BUITEN DRAAIENDE DEUREN MET DUBBELE VLEUGEL EN TOCHTRUBBER



raamSELECT NV
Merksplassesteenweg 18
2310 Rijkevorsel

Aangegeven prestaties volgens
NBN EN 14351-1:2006+A2:2016



Characteristic			Performance	Notified body - Report	Tested size [mm]
Essential characteristics					
EN 14351-1	4.2	Resistance to wind load	C3 (1200 Pa)	[0960] – 25.00897 ^(A)	888 x 2363
	4.5	Watertightness	npd		
	4.6	Dangerous substances	In the materials delivered by Reynaers, no dangerous substances as indicated in hEN 14351-1 are used.		
	4.7	Impact resistance	5 (950 mm)	[0960] – 09.1169 *	642 x 1758
	4.8	Load-bearing capacity of safety devices	npd		
	4.9	Height & width	See 6		
	4.11	Acoustic performance	npd		
	4.12	Thermal transmittance	Ud to be calculated in function of the project. Pre-calculated U-values for dimensions 2000x2180mm can be found in the Uf-value tables. Uf-values are calculated under certification of BCCA: certificate BPCB-420-72-10077/2.		
	4.13	Radiation properties	These properties must be evaluated by the CE-label of the glass		
	4.14	Air permeability	npd		

Non-essential characteristics					
EN 14351-1	4.4.1	Reaction to fire	Anodized: A1 Painted: A2 Gaskets: E	EC decision 96/603/EC [1812] - EFR-21-001664A [0432] – 230006500-6	
	4.16	Operating forces	2 1	[0960] – 22.00087.2 ^[A] [0960] – 24.00379 ^[B]	1100x2400, 179 kg 1168x2763, 131 kg
	4.17	Mechanical strength	3	[0960] – 24.00379.1 ^[B]	1168x2763, 131 kg
	4.18	Ventilation	npd		
	4.19	Bullet resistance (BP version)	npd		
	4.20	Explosion resistance	npd		
	4.21	Resistance to repeated opening and closing	6 (200.000) 4 (50.000)	[0960] – 22.00087.2 ^[A] [0960] – 24.00379 ^[B]	1100x2400, 179 kg 1168x2763, 131 kg
	4.22	Behaviour between different climates	npd		
	4.23	Burglar resistance (AP version)	RC2	[0960] – SKG.0837.0232 ^[A]	See report

De prestaties van de producten die met bovenstaande unieke identificatiecodes zijn aangeduid, zijn in overeenstemming met de betreffende opgegeven prestaties. Deze prestatieverklaring wordt afgegeven onder de uitsluitende verantwoordelijkheid van raamSELECT

Voor en namens de fabrikant ondertekend door :

Naam en functie	Plaats en datum van afgifte	Handtekening
Stijn Hoskens (directeur)	01/07/2026	