




PRESTATIEVERKLARING

REYNAERS RAMEN – SL38

Nr. R-03

d.d. 01/07/2026

Productnaam	Ramen vervaardigd uit de profielsystemen : Reynaers SL38			
Type aanduiding	<5.1> Naar binnen draaiende ramen met enkele vleugel <5.2> Naar binnen draaiende ramen met dubbele vleugel <5.3> Naar binnen draaiende ramen met enkele vleugel en vast gedeelte <5.4> Naar buiten draaiende ramen met enkele vleugel <5.5> Naar buiten draaiende ramen met dubbele vleugel <5.6> Naar binnen draaiende balkondeuren met enkele vleugel <5.7> Naar binnen draaiende balkondeuren met dubbele vleugel			
Toepassing	Reynaers ramen SL38 voor toepassing in woningen en utiliteitsgebouwen zonder brand- en rookwerende eigenschappen.			
Naam en contactadres fabrikant	raamSELECT NV Merksplassesteenweg 18 2310 Rijkevorsel			
Naam en contactadres gemachtigde	Niet van toepassing			
Systeem voor de beoordeling en verificatie van de prestatiebestendigheid	AVCP 3			
Activiteit van de aangemelde certificatie instantie volgens NBN EN 14351-1:2006+A2:2016	ID	Name	Address	Country
	0074	CENTRE D'EXPERTISE DU BÂTIMENT ET DES TRAVAUX PUBLICS	Domaine De Saint-Paul – 102, Route de Limours 78471 Saint-Remy-Les-Chevreuse Cedex	France
	0336	TÜV RHEINLAND NEDERLAND	Westervoortsedijk 73 6827 AV Arnhem	Netherlands
	0432	MATERIALPRÜFUNGSAMT NORDRHEIN-WESTFALEN	Auf den Thronen 2 59597 Erwitte	Germany
	0679	CENTRE SCIENTIFIQUE ET TECHNIQUE DU BÂTIMENT	84, Avenue Jean Jaurès Champs-sur-Marne F-77447 Mame-la-Vallée Cedex 2	France
	0744	SOCOTEC	Les Quadrants – 3, Avenue du Centre – Guyancourt 78182 St-Quentin en Yvelines	France
	0749	BELGIAN CONSTRUCTION CERTIFICATION ASSOCIATION	Aarlenstraat 53 1040 Brussel	Belgium
	0757	IFT ROSENHEIM	Theodor-Giell-Strasse 7-9 83026 Rosenheim	Germany
	0845	DANISH INSTITUTE OF FIRE AND SECURITY TECHNOLOGY	Jernholmen, 12 2650 Hvidovre	Denmark
	0960	SKG-IKOB	Poppenbouwing 56 4191 NZ Geldermalsen	Netherlands
	1136	BELGIAN BUILDING RESEARCH INSITUTE	Lombardstraat 42 1000 Brussel	Belgium
	1234	EFFECTIS NEDERLAND	Brandpuntlaan Zuid 16, Postbus 554 2665 ZN Bleiswijk	Netherlands
	1288	WINTech ENGINEERING LIMITED	Halesfield 2 Telford, Shropshire TF7 4QH	United Kingdom
	1309	PRÜFINSTITUT SCHLÖSSER UND BESCHLÄGE, VELBERT	Wallstrasse 41 42551 Velbert	Germany
	1488	INSTYTUT TECHNIKI BUDOWLANEJ	ul. Filtrów 1 00-611 Warszawa	Poland
	1671	PEUTZ	Lindenlaan 41, Molenhoek PO Box 66 6585 ZH MOOK	Netherlands
	1749	TNO DEFENCE, SECURITY AND SAFETY	Lange Kleiweg 137, Postbus 45 2280 AA Rijswijk	Netherlands
	1769	UNIVERSITY OF GENT	Sint-Pietersnieuwstraat 41 9000 Gent	Belgium
	1812	EFFECTIS FRANCE	ZI. Les Nappes 149, route du Marc 38630 Les Aveniers Veyrins-Thuellin	France
	2211	INSTITUTO DE INVESTIGAÇÃO E DESENVOLVIMENTO TECNOLÓGICO PARA A CONSTRUÇÃO, ENERGIA, AMBIENTE E SUSTENTABILIDADE	Rua Pedro Hispano Pólo II da Universidade de Coimbra 3030-289 Coimbra	Portugal
	2434	CENTRUM TECHNIKI OKRĘTOWEJ	ul. Szczecińska 65 80-392 Gdańsk	Poland
	2509	DMT	Hermann-Kemper-Str. 12a 42699 Solingen	Germany

Namens het management van	Datum	Naam	Handtekening
raamSELECT NV	01/07/2026	Stijn Hoskens	

<5.1> NAAR BINNEN DRAAIENDE RAMEN MET ENKELE VLEUGEL



raamSELECT NV
Merksplassesteenweg 18
2310 Rijkevorsel

Aangegeven prestaties volgens
NBN EN 14351-1:2006+A2:2016




Characteristic			Performance		Notified body - Report	Tested size [mm]
Essential characteristics						
EN 14351-1	4.2	Resistance to wind load	C3 (1200 Pa) C4 (1600 Pa) C4 (1600 Pa) C4 (1600 Pa) C4 (1600 Pa)		[0960] – 15.00785 [0960] – 24.01312 [0960] – 25.01721 [2211] - CXL 051/25 [0960] – 20.00220	1400 x 2400 1300 x 1950 1200 x 3000 1150 x 1750 2000 x 2400 *
	4.5	Watertightness	9A (600 Pa) E900 (900 Pa) E900 (900 Pa) 9A (600 Pa) 9A (600 Pa)		[0960] – 15.00785 [0960] – 24.01312 [0960] – 25.01721 [2211] - CXL 051/25 [0960] – 20.00220	1400 x 2400 1300 x 1950 1200 x 3000 1150 x 1750 2000 x 2400 *
	4.6	Dangerous substances	In the materials delivered by Reynaers, no dangerous substances as indicated in hEN 14351-1 are used.			
	4.8	Load-bearing capacity of safety devices	Pass		[0960] – 15.00689	1400 x 2400
	4.11	Acoustic performance	Glass: 40 (-1;-3) 45 (-2;-6) 50 (-3;-8)	Window: 38 (-1;-4) 42 (-1;-5) 45 (-1;-5)	[0960] – 15.00643-1 [0960] – 15.00643-2 [0960] – 15.00643-3	1230 x 1480
	4.12	Thermal transmittance	Uw to be calculated in function of the project. Pre-calculated U-values for dimensions 1230x1480mm and 1480x2180 can be found in the Uf-value tables. Uf-values are calculated under certification of BCCA: certificate BPCB-420-72-10077/2.			
	4.13	Radiation properties	These properties must be evaluated by the CE-label of the glass			
	4.14	Air permeability	4		[0960] – 15.00785 [0960] – 24.01312 [0960] – 25.01721 [2211] - CXL 051/25 [0960] – 20.00220	1400 x 2400 1300 x 1950 1200 x 3000 1150 x 1750 2000 x 2400 *

Non-essential characteristics					
EN 14351-1	4.4.1	Reaction to fire	Anodized: A1 Painted: A2 Gaskets: E	EC decision 96/603/EC [1812] - EFR-21-001664A [0432] - 230006500-6	
	4.7	Impact resistance	Npd		
	4.16	Operating forces	1 1 2	[0960] - 15.00689 [2211] - CXL 050/25 [0960] - 25.01758	1400 x 2400, 166 kg 1150 x 1750, 46 kg 800 x 2800, 142 kg
	4.17	Mechanical strength	4	[0960] - 15.00689 [2211] - CXL 073+074/25 [0960] - 26.00031	1400 x 2400, 166 kg 1400 x 2400, 141 kg 800 x 2800, 142 kg
	4.18	Ventilation	Npd		
	4.19	Bullet resistance (BP version)	Npd		
	4.20	Explosion resistance	Npd		
	4.21	Resistance to repeated opening and closing	3 (20.000)	[0960] - 15.00689 [2211] - CXL 104/25 [0960] - 25.01758	1400 x 2400, 166 kg 1400 x 2400, 160 kg 800 x 2800, 142 kg
	4.22	Behaviour between different climates	Npd		
	4.23	Burglar resistance (AP version)	RC 2	[0960] - SKG.0837.0232 [1136] - GSFM-22-195-07	See report

* Valid for a fixed window

De prestaties van de producten die met bovenstaande unieke identificatiecodes zijn aangeduid, zijn in overeenstemming met de betreffende opgegeven prestaties. Deze prestatieverklaring wordt afgegeven onder de uitsluitende verantwoordelijkheid van raamSELECT


Voor en namens de fabrikant ondertekend door :

Naam en functie	Plaats en datum van afgifte	Handtekening
Stijn Hoskens (directeur)	01/07/2026	

<5.2> NAAR BINNEN DRAAIENDE RAMEN MET DUBBELE VLEUGEL

raamSELECT NV
 Merksplassesteenweg 18
 2310 Rijkevorsel

Aangegeven prestaties volgens
NBN EN 14351-1:2006+A2:2016




Characteristic			Performance		Notified body - Report	Tested size [mm]
Essential characteristics						
EN 14351-1	4.2	Resistance to wind load	C3 (1200 Pa) C2 (800 Pa)		[0960] – 15.00671 [0960] – 16.00720.1	1150 x 2200 771 x 1389
	4.5	Watertightness	8A (450 Pa) 9A (600 Pa)		[0960] – 15.00671 [0960] – 16.00720.1	1150 x 2200 771 x 1389
	4.6	Dangerous substances	In the materials delivered by Reynaers, no dangerous substances as indicated in hEN 14351-1 are used.			
	4.8	Load-bearing capacity of safety devices	Pass		[0960] – 16.00976	777 x 2358
	4.11	Acoustic performance	Glass: 36 (-1;-5) 41 (-2;-4) 45 (-2;-6) 50 (-2;-8) 52 (-1;-5)	Window: 37 (-1;-4) 40 (-2;-4) 43 (-1;-4) 46 (-2;-5) 46 (-1;-4)	[0960] – 24.00482.1 [0960] – 24.00482.2 [0960] – 24.00482.3 [0960] – 24.00482.4 [0960] – 24.00482.5	1230 x 1480
	4.12	Thermal transmittance	Uw to be calculated in function of the project. Uf-values are calculated under certification of BCCA: certificate BPCB-420-72-10077/2.			
	4.13	Radiation properties	These properties must be evaluated by the CE-label of the glass			
	4.14	Air permeability	4		[0960] – 15.00671 [0960] – 16.00720.1	1150 x 2200 771 x 1389

Non-essential characteristics					
EN 14351-1	4.4.1	Reaction to fire	Anodized: A1 Painted: A2 Gaskets: E	EC decision 96/603/EC [1812] - EFR-21-001664A [0432] - 230006500-6	
	4.7	Impact resistance	Npd		
	4.16	Operating forces	1 0	[0960] - 15.00554 [0960] - 16.00976	1300 x 1750, 49 kg 777 x 2358, 180 kg
	4.17	Mechanical strength	1 4	[0960] - 15.00554 [0960] - 16.00976	1300 x 1750, 49 kg 777 x 2358, 180 kg
	4.18	Ventilation	npd		
	4.19	Bullet resistance (BP version)	npd		
	4.20	Explosion resistance	npd		
	4.21	Resistance to repeated opening and closing	3 (20.000)	[0960] - 15.00554 [0960] - 16.00976	1300 x 1750, 49 kg 777 x 2358, 180 kg
	4.22	Behaviour between different climates	npd		
	4.23	Burglar resistance (AP version)	RC 2	[0960] - SKG.0837.0232 [1136] - GSFM-22-195-07	See report

De prestaties van de producten die met bovenstaande unieke identificatiecodes zijn aangeduid, zijn in overeenstemming met de betreffende opgegeven prestaties. Deze prestatieverklaring wordt afgegeven onder de uitsluitende verantwoordelijkheid van raamSELECT

Voor en namens de fabrikant ondertekend door :

Naam en functie	Plaats en datum van afgifte	Handtekening
Stijn Hoskens (directeur)	01/07/2026	

<5.3> NAAR BINNEN DRAAIENDE RAMEN MET ENKELE VLEUGEL EN VAST GEDEELTE



raamSELECT NV
Merksplassesteenweg 18
2310 Rijkevorsel

Aangegeven prestaties volgens
NBN EN 14351-1:2006+A2:2016




Characteristic			Performance	Notified body - Report	Tested size [mm]
Essential characteristics					
EN 14351-1	4.2	Resistance to wind load	C3 (1200 Pa) ⁽¹⁾ C4 (1600 Pa) ⁽¹⁾	[0960] – 20.00746 [0960] – 19.00621	(3)
	4.5	Watertightness	7A (300 Pa) 9A (600 Pa)	[0960] – 20.00746 ⁽²⁾ [0960] – 19.00621 ⁽²⁾	(3)
	4.6	Dangerous substances	In the materials delivered by Reynaers, no dangerous substances as indicated in hEN 14351-1 are used.		
	4.8	Load-bearing capacity of safety devices	See relevant test reports for opening parts		
	4.11	Acoustic performance	npd (See 6)		
	4.12	Thermal transmittance	Uw to be calculated in function of the project. Uf-values are calculated under certification of BCCA: certificate BPCB-420-72-10077/2.		
	4.13	Radiation properties	These properties must be evaluated by the CE-label of the glass		
	4.14	Air permeability	4	[0960] – 20.00746 [0960] – 19.00621	(3)

Non-essential characteristics					
EN 14351-1	4.4.1	Reaction to fire	Anodized: A1 Painted: A2 Gaskets: E	EC decision 96/603/EC [1812] - EFR-21-001664A [0432] – 230006500-6	
	4.7	Impact resistance	npd		
	4.16	Operating forces	See relevant test reports for opening parts		
	4.17	Mechanical strength	See relevant test reports for opening parts		
	4.18	Ventilation	npd		
	4.19	Bullet resistance (BP version)	npd		
	4.20	Explosion resistance	npd		
	4.21	Resistance to repeated opening and closing	See relevant test reports for opening parts		
	4.22	Behaviour between different climates	npd		
	4.23	Burglar resistance (AP version)	RC 2	[0960] – SKG.0837.0232 [1136] – GSFM-22-195-07	See report

De prestaties van de producten die met bovenstaande unieke identificatiecodes zijn aangeduid, zijn in overeenstemming met de betreffende opgegeven prestaties. Deze prestatieverklaring wordt afgegeven onder de uitsluitende verantwoordelijkheid van raamSELECT

Voor en namens de fabrikant ondertekend door :

Naam en functie	Plaats en datum van afgifte	Handtekening
Stijn Hoskens (directeur)	01/07/2026	

<5.4> NAAR BUITEN DRAAIENDE RAMEN MET ENKELE VLEUGEL


raamSELECT NV
 Merksplassesteenweg 18
 2310 Rijkevorsel

Aangegeven prestaties volgens
NBN EN 14351-1:2006+A2:2016




Characteristic			Performance	Notified body - Report	Tested size [mm]
Essential characteristics					
EN 14351-1	4.2	Resistance to wind load	C3 (1200 Pa)	[0960] – 22.00310	1100 x 2300
	4.5	Watertightness	E900 (900 Pa)	[0960] – 22.00310	1100 x 2300
	4.6	Dangerous substances	In the materials delivered by Reynaers, no dangerous substances as indicated in hEN 14351-1 are used.		
	4.8	Load-bearing capacity of safety devices	Npd		
	4.11	Acoustic performance	npd (See 6)		
	4.12	Thermal transmittance	Uw to be calculated in function of the project. Uf-values are calculated under certification of BCCA: certificate BPCB-420-72-10077/2.		
	4.13	Radiation properties	These properties must be evaluated by the CE-label of the glass		
	4.14	Air permeability	4	[0960] – 22.00310	1100 x 2300

Non-essential characteristics					
EN 14351-1	4.4.1	Reaction to fire	Anodized: A1 Painted: A2 Gaskets: E	EC decision 96/603/EC [1812] - EFR-21-001664A [0432] - 230006500-6	
	4.7	Impact resistance	Npd		
	4.16	Operating forces	1	[0960] - 22.00175	800 x 2200, 53 kg
	4.17	Mechanical strength	Npd		
	4.18	Ventilation	npd		
	4.19	Bullet resistance (BP version)	npd		
	4.20	Explosion resistance	npd		
	4.21	Resistance to repeated opening and closing	3 (20.000)	[0960] - 22.00175	800 x 2200, 53 kg
	4.22	Behaviour between different climates	npd		
	4.23	Burglar resistance (AP version)	npd		

De prestaties van de producten die met bovenstaande unieke identificatiecodes zijn aangeduid, zijn in overeenstemming met de betreffende opgegeven prestaties. Deze prestatieverklaring wordt afgegeven onder de uitsluitende verantwoordelijkheid van raamSELECT

Voor en namens de fabrikant ondertekend door :

Naam en functie	Plaats en datum van afgifte	Handtekening
Stijn Hoskens (directeur)	01/07/2026	

<5.5> NAAR BUITEN DRAAIENDE RAMEN MET DUBBELE VLEUGEL

raamSELECT NV
Merksplassesteenweg 18
2310 Rijkevorsel


Aangegeven prestaties volgens
NBN EN 14351-1:2006+A2:2016



Characteristic			Performance	Notified body - Report	Tested size [mm]
Essential characteristics					
EN 14351-1	4.2	Resistance to wind load	C3 (1200 Pa)	[0960] – 22.00498 [0960] – 26.00391	1100 x 2300 837 x 2000
	4.5	Watertightness	E750 (750 Pa) 9A (600 Pa)	[0960] – 22.00498 [0960] – 26.00391	1100 x 2300 837 x 2000
	4.6	Dangerous substances	In the materials delivered by Reynaers, no dangerous substances as indicated in hEN 14351-1 are used.		
	4.8	Load-bearing capacity of safety devices	npd		
	4.11	Acoustic performance	npd		
	4.12	Thermal transmittance	Uw to be calculated in function of the project. Uf-values are calculated under certification of BCCA: certificate BPCB-420-72-10077/2.		
	4.13	Radiation properties	These properties must be evaluated by the CE-label of the glass		
	4.14	Air permeability	4	[0960] – 22.00498 [0960] – 26.00391	1100 x 2300 837 x 2000

Non-essential characteristics					
EN 14351-1	4.4.1	Reaction to fire	Anodized: A1 Painted: A2 Gaskets: E	EC decision 96/603/EC [1812] - EFR-21-001664A [0432] – 230006500-6	
	4.7	Impact resistance	npd		
	4.16	Operating forces	npd		
	4.17	Mechanical strength	npd		
	4.18	Ventilation	npd		
	4.19	Bullet resistance (BP version)	npd		
	4.20	Explosion resistance	npd		
	4.21	Resistance to repeated opening and closing	npd		
	4.22	Behaviour between different climates	npd		
	4.23	Burglar resistance (AP version)	npd		

De prestaties van de producten die met bovenstaande unieke identificatiecodes zijn aangeduid, zijn in overeenstemming met de betreffende opgegeven prestaties. Deze prestatieverklaring wordt afgegeven onder de uitsluitende verantwoordelijkheid van raamSELECT
Voor en namens de fabrikant ondertekend door :

Naam en functie	Plaats en datum van afgifte	Handtekening
Stijn Hoskens (directeur)	01/07/2026	

<5.6> NAAR BINNEN DRAAIENDE BALKONDEUREN MET ENKELE VLEUGEL


raamSELECT NV
Merksplassesteenweg 18
2310 Rijkevorsel

Aangegeven prestaties volgens
NBN EN 14351-1:2006+A2:2016




Characteristic			Performance	Notified body - Report	Tested size [mm]
Essential characteristics					
EN 14351-1	4.2	Resistance to wind load	C4 (1600 Pa) C3 (1200 Pa)	[0960] – 22.00725 * [0960] – 24.01560 *	1142 x 2460 1100 x 2250
	4.5	Watertightness	9A (600 Pa) E900 (900 Pa)	[0960] – 22.00725 * [0960] – 24.01560 *	1142 x 2460 1100 x 2250
	4.6	Dangerous substances	In the materials delivered by Reynaers, no dangerous substances as indicated in hEN 14351-1 are used.		
	4.8	Load-bearing capacity of safety devices	npd		
	4.11	Acoustic performance	npd		
	4.12	Thermal transmittance	Ud to be calculated in function of the project. Pre-calculated U-values for dimensions 1230x2180mm can be found in the Uf-value tables. Uf-values are calculated under certification of BCCA: certificate BPCB-420-72-10077/2.		
	4.13	Radiation properties	These properties must be evaluated by the CE-label of the glass		
	4.14	Air permeability	4	[0960] – 22.00725 * [0960] – 24.01560 *	1142 x 2460 1100 x 2250

Non-essential characteristics				
EN 14351-1	4.4.1	Reaction to fire	Anodized: A1 Painted: A2 Gaskets: E	EC decision 96/603/EC [1812] - EFR-21-001664A [0432] - 230006500-6
	4.7	Impact resistance	npd	
	4.16	Operating forces	1	[0960] - 22.00445 1142 x 2763, 136 kg
	4.17	Mechanical strength	4	[0960] - 22.00445 1142 x 2763, 136 kg
	4.18	Ventilation	Npd	
	4.19	Bullet resistance (BP version)	Npd	
	4.20	Explosion resistance	Npd	
	4.21	Resistance to repeated opening and closing	3 (20.000)	[0960] - 22.00445 1142 x 2763, 136 kg
	4.22	Behaviour between different climates	Npd	
	4.23	Burglar resistance (AP version)	RC 2	[0960] - SKG.0837.0232 [1136] - GSFM-22-195-07 See report

De prestaties van de producten die met bovenstaande unieke identificatiecodes zijn aangeduid, zijn in overeenstemming met de betreffende opgegeven prestaties. Deze prestatieverklaring wordt afgegeven onder de uitsluitende verantwoordelijkheid van raamSELECT


Voor en namens de fabrikant ondertekend door :

Naam en functie	Plaats en datum van afgifte	Handtekening
Stijn Hoskens (directeur)	01/07/2026	

<5.7> NAAR BINNEN DRAAIENDE BALKONDEUREN MET DUBBELE VLEUGEL


raamSELECT NV
Merksplassesteenweg 18
2310 Rijkevorsel

Aangegeven prestaties volgens
NBN EN 14351-1:2006+A2:2016



Characteristic			Performance	Notified body - Report	Tested size [mm]
Essential characteristics					
EN 14351-1	4.2	Resistance to wind load	C3 (1200 Pa)	[0960] – 24.00889 * [0960] – 24.00940 *	1100 x 2250
	4.5	Watertightness	8A (450 Pa) E900 (900 pa)	[0960] – 24.00889 * [0960] – 24.00940 *	1100 x 2250
	4.6	Dangerous substances	In the materials delivered by Reynaers, no dangerous substances as indicated in hEN 14351-1 are used.		
	4.8	Load-bearing capacity of safety devices	npd		
	4.11	Acoustic performance	npd		
	4.12	Thermal transmittance	Ud to be calculated in function of the project. Pre-calculated U-values for dimensions 2000x2180mm can be found in the Uf-value tables. Uf-values are calculated under certification of BCCA: certificate BPCB-420-72-10077/2.		
	4.13	Radiation properties	These properties must be evaluated by the CE-label of the glass		
	4.14	Air permeability	4	[0960] – 24.00889 * [0960] – 24.00940 *	1100 x 2250

Non-essential characteristics					
EN 14351-1	4.4.1	Reaction to fire	Anodized: A1 Painted: A2 Gaskets: E	EC decision 96/603/EC [1812] - EFR-21-001664A [0432] – 230006500-6	
	4.7	Impact resistance	npd		
	4.16	Operating forces	1	[0960] – 22.00445	1142 x 2763, 136 kg
	4.17	Mechanical strength	4	[0960] – 22.00445	1142 x 2763, 136 kg
	4.18	Ventilation	Npd		
	4.19	Bullet resistance (BP version)	Npd		
	4.20	Explosion resistance	Npd		
	4.21	Resistance to repeated opening and closing	3 (20.000)	[0960] – 22.00445	1142 x 2763, 136 kg
	4.22	Behaviour between different climates	Npd		
	4.23	Burglar resistance (AP version)	RC 2	[0960] – SKG.0837.0232 [1136] – GSFM-22-195-07	See report

De prestaties van de producten die met bovenstaande unieke identificatiecodes zijn aangeduid, zijn in overeenstemming met de betreffende opgegeven prestaties. Deze prestatieverklaring wordt afgegeven onder de uitsluitende verantwoordelijkheid van raamSELECT

Voor en namens de fabrikant ondertekend door :

Naam en functie	Plaats en datum van afgifte	Handtekening
Stijn Hoskens (directeur)	01/07/2026	