




PRESTATIEVERKLARING

REYNAERS SCHUIFRAMEN – CP130 LS

Nr. R-05 **d.d. 01/07/2026**

Productnaam	Schuiframen vervaardigd uit de profielsystemen : Reynaers CP130 LS			
Type aanduiding	<5.1> Duorail hefschuifraam <5.2> Monorail hefschuifraam <5.3> 3-rail hefschuifraam <5.4> 4-rail hefschuifraam			
Toepassing	Reynaers schuiframen CP130 LS voor toepassing in woningen en utiliteitsgebouwen zonder brand- en rookwerende eigenschappen.			
Naam en contactadres fabrikant	raamSELECT NV Merksplassesteenweg 18 2310 Rijkvorsel			
Naam en contactadres gemachtigde	Niet van toepassing			
Systeem voor de beoordeling en verificatie van de prestatiebestendigheid	AVCP 3			
Activiteit van de aangemelde certificatie-instantie volgens NBN EN 14351-1:2006+A2:2016	ID	Name	Address	Country
	0074	CENTRE D'EXPERTISE DU BÂTIMENT ET DES TRAVAUX PUBLICS	Domaine De Saint-Paul – 102, Route de Limours 78471 Saint-Remy-Les-Chevreuse Cedex	France
	0336	TÜV RHEINLAND NEDERLAND	Westervoortsedijk 73 6827 AV Arnhem	Netherlands
	0432	MATERIALPRÜFUNGSAMT NORDRHEIN-WESTFALEN	Auf den Thränen 2 59597 Erwitte	Germany
	0679	CENTRE SCIENTIFIQUE ET TECHNIQUE DU BÂTIMENT	84, Avenue Jean Jaurès Champs-sur-Marne F-77447 Marne-la-Vallée Cedex 2	France
	0744	SOCOTEC	Les Quadrants – 3, Avenue du Centre – Guyancourt 78182 St-Quentin en Yvelines	France
	0749	BELGIAN CONSTRUCTION CERTIFICATION ASSOCIATION	Aarlenstraat 53 1040 Brussel	Belgium
	0757	IFT ROSENHEIM	Theodor-Gießl-Strasse 7-9 83026 Rosenheim	Germany
	0845	DANISH INSTITUTE OF FIRE AND SECURITY TECHNOLOGY	Jernholmen, 12 2650 Hvidovre	Denmark
	0960	SKG-IKOB	Poppenbouwing 56 4191 NZ Geldermalsen	Netherlands
	1136	BELGIAN BUILDING RESEARCH INSITUTE	Lombardstraat 42 1000 Brussel	Belgium
	1234	EFFECTIS NEDERLAND	Brandpuntlaan Zuid 16, Postbus 554 2665 ZN Bleiswijk	Netherlands
	1288	WINTech ENGINEERING LIMITED	Halesfield 2 Telford, Shropshire TF7 4QH	United Kingdom
	1309	PRÜFINSTITUT SCHLÖSSER UND BESCHLÄGE, VELBERT	Wallstrasse 41 42551 Velbert	Germany
	1488	INSTYTUT TECHNIKI BUDOWLANEJ	ul. Filtrowa 1 00-611 Warszawa	Poland
	1671	PEUTZ	Lindenlaan 41, Molenhoek PO Box 66 6585 ZH MOOK	Netherlands
	1749	TNO DEFENCE, SECURITY AND SAFETY	Lange Kleiweg 137, Postbus 45 2280 AA Rijswijk	Netherlands
	1769	UNIVERSITY OF GENT	Sint-Pietersnieuwstraat 41 9000 Gent	Belgium
	1812	EFFECTIS FRANCE	ZI. Les Nappes 149, route du Marc 38630 Les Aveniers Veyrins-Thuellin	France
	2211	INSTITUTO DE INVESTIGAÇÃO E DESENVOLVIMENTO TECNOLÓGICO PARA A CONSTRUÇÃO, ENERGIA, AMBIENTE E SUSTENTABILIDADE	Rua Pedro Hispano Pólo II da Universidade de Coimbra 3030-289 Coimbra	Portugal
	2434	CENTRUM TECHNIKI OKRĘTOWEJ	ul. Szczecińska 65 80-392 Gdańsk	Poland
	2509	DMT	Hermann-Kemper-Str. 12a 42699 Solingen	Germany

Namens het management van	Datum	Naam	Handtekening
raamSELECT NV	01/07/2026	Stijn Hoskens	

<5.1> DUORAIL HEFSCHUIFRAAM




raamSELECT NV
Merksplassesteenweg 18
2310 Rijkevorsel

Aangegeven prestaties volgens
NBN EN 14351-1:2006+A2:2016



Characteristic			Performance		Notified body - Report	Tested size [mm]
Essential characteristics						
EN 14351-1	4.2	Resistance to wind load	C2 (800 Pa) ⁽¹⁾ B5 (2000 Pa) ⁽¹⁾		[0960] – 18.00277 rev A [0960] – 20.00072 *	1510x2633 ⁽³⁾ 1486x2633 ⁽³⁾
	4.5	Watertightness	9A (600 Pa) 7A (300 Pa)		[0960] – 18.00277 rev A [0960] – 20.00072 *	1510x2633 1486x2633
	4.6	Dangerous substances	In the materials delivered by Reynaers, no dangerous substances as indicated in hEN 14351-1 are used.			
	4.7	Impact resistance	5		[0960] – SKG/HRU/cbo/10.0099-3	821x1729
	4.8	Load-bearing capacity of safety devices	npd			
	4.9	Height & width	See 6			
	4.11	Acoustic performance	Glass: 35 (-2;-6) 41 (-2;-4) 45 (-2;-6) 52 (-1;-5)	Sliding door: 34 (-1;-4) 37 (-1;-4) 39 (-1;-3) 40 (-1;-3)	[0960] – 11.156-Rev A [0960] – 11.156-Rev A [1671] – A 3378-1E-RA-002 [1671] – A 3378-1E-RA-002	4090x2334 4090x2334 4050x2350 4050x2350
	4.12	Thermal transmittance	Ud to be calculated in function of the project. Uf-values are calculated under certification of BCCA: certificate BPCB-420-72-10077/2.			
	4.13	Radiation properties	These properties must be evaluated by the CE-label of the glass			
	4.14	Air permeability	4		[0960] – 24.00758 [0960] – 18.00277 rev A [0960] – 20.00072 *	1510x2633 1510x2633 1486x2633

Non-essential characteristics				
EN 14351-1	4.4.1	Reaction to fire	Anodized: A1 Painted: A2 Gaskets: E	EC decision 96/603/EC certificate EFR-21-001664A [0432] – 230006500-6
	4.16	Operating forces	2 1	[1488] – LK-02344/09/9/part 1 ⁽⁴⁾ [0960] – 21.00400 rev A
	4.17	Mechanical strength	4	[0960] – 18.00277.1 rev A
	4.18	Ventilation	npd	
	4.19	Bullet resistance (BP version)	npd	
	4.20	Explosion resistance	npd	
	4.21	Resistance to repeated opening and closing	4 (50.000) 3 (20.000)	[0960] – 09.1125 ⁽⁴⁾ [0960] – 21.00400 rev A
	4.22	Behaviour between different climates	npd	
	4.23	Burglar resistance (AP version)	RC 2	[1136] – CAR 10257/3 [1136] – GSFM-20-071
				See report



Characteristic			Performance		Notified body - Report	Tested size [mm]
Essential characteristics						
EN 14351-1	4.2	Resistance to wind load	B3 (1200 Pa) ⁽¹⁾		[0960] – 16.00974	1510x2633 ⁽³⁾
	4.5	Watertightness	8A (450 Pa)		[0960] – 16.00974	1510x2633
	4.6	Dangerous substances	In the materials delivered by Reynaers, no dangerous substances as indicated in hEN 14351-1 are used.			
	4.7	Impact resistance	5		[0960] – SKG/HRU/cbo/10.0099-3	821x1729
	4.8	Load-bearing capacity of safety devices	npd			
	4.9	Height & width	See 6			
	4.11	Acoustic performance	Glass: 35 (-2;-6) 41 (-2;-4) 45 (-2;-6) 50 (-3;-8)	Sliding door: 34 (-1;-4) 37 (-1;-4) 39 (-1;-3) 39 (-1;-3)	[0960] – 11.156-Rev A	4090x2334
	4.12	Thermal transmittance	Ud to be calculated in function of the project. Uf-values are calculated under certification of BCCA: certificate BPCB-420-72-10077/2.			
	4.13	Radiation properties	These properties must be evaluated by the CE-label of the glass			
	4.14	Air permeability	4		[0960] – 16.00974	1510x2633

Non-essential characteristics					
EN 14351-1	4.4.1	Reaction to fire	Anodized: A1 Painted: A2 Gaskets: E	EC decision 96/603/EC certificate EFR-21-001664A [0432] – 230006500-6	
	4.16	Operating forces	2	[1488] – LK-02344/09/9/part 1 ⁽⁴⁾	1101x2229, 66 kg
			1	[0960] – 21.00400 rev A	2300x2700, 300/400 kg
	4.17	Mechanical strength	4	[0960] – 18.00277.1 rev A	1510x2633, 171 kg
	4.18	Ventilation	npd		
	4.19	Bullet resistance (BP version)	npd		
	4.20	Explosion resistance	npd		
	4.21	Resistance to repeated opening and closing	4 (50.000) 3 (20.000)	[0960] – 09.1125 ⁽⁴⁾ [0960] – 21.00400 rev A	1428x2219, 150 kg 2300x2700, 300/400 kg
	4.22	Behaviour between different climates	npd		
	4.23	Burglar resistance (AP version)	RC 2	[1136] – CAR 10257/3 [1136] – GSFM-20-071	See report

De prestaties van de producten die met bovenstaande unieke identificatiecodes zijn aangeduid, zijn in overeenstemming met de betreffende opgegeven prestaties. Deze prestatieverklaring wordt afgegeven onder de uitsluitende verantwoordelijkheid van raamSELECT

Voor en namens de fabrikant ondertekend door :


Naam en functie	Plaats en datum van afgifte	Handtekening
Stijn Hoskens (directeur)	01/07/2026	

<5.2> MONORAIL HEFSCHUIFRAAM




raamSELECT NV
 Merksplassesteenweg 18
 2310 Rijkevorsel

Aangegeven prestaties volgens
NBN EN 14351-1:2006+A2:2016




Characteristic			Performance		Notified body - Report		Tested size [mm]	
Essential characteristics								
EN 14351-1	4.2	Resistance to wind load	C3 (1200 Pa) ⁽¹⁾ B5 (2000 Pa) ⁽¹⁾		[0960] – 23.00205 [0960] - 20.00072 **		1500x2700 ⁽³⁾ 1486x2633 ⁽³⁾	
	4.5	Watertightness	E750 (750 Pa)		[0960] – 23.00205		1500x2700	
	4.6	Dangerous substances	In the materials delivered by Reynaers, no dangerous substances as indicated in hEN 14351-1 are used.					
	4.7	Impact resistance	5		[0960] – SKG/HRU/cbo/10.0099-3		821x1729	
	4.8	Load-bearing capacity of safety devices	npd					
	4.9	Height & width	See 6					
	4.11	Acoustic performance	Glass: 36 (-1;-5) 41 (-2;-4) 45 (-2;-6) 50 (-2;-8)	Sliding door: 34 (-1;-4) 38 (-1;-4) 42 (-1;-4) 45 (-1;-5)	[0749] – AC-23-050-02 [0749] – AC-23-050-03 [0749] – AC-23-050-10 * [0749] – AC-23-050-07 *		2705x2360	
	4.12	Thermal transmittance	Ud to be calculated in function of the project. Uf-values are calculated under certification of BCCA: certificate BPCB-420-72-10077/2.					
	4.13	Radiation properties	These properties must be evaluated by the CE-label of the glass					
	4.14	Air permeability	4		[0960] – 23.00205		1500x2700	

Non-essential characteristics					
EN 14351-1	4.4.1	Reaction to fire	Anodized: A1 Painted: A2 Gaskets: E	EC decision 96/603/EC certificate EFR-21-001664A [0432] – 230006500-6	
	4.16	Operating forces	1	[0960] – 23.00437.1 [0960] – 21.00400 rev A	2000x2700, 250 kg 2300x2700, 300/400 kg
	4.17	Mechanical strength	4	[0960] – 18.00277.1 rev A	1510x2633, 171 kg
	4.18	Ventilation	npd		
	4.19	Bullet resistance (BP version)	npd		
	4.20	Explosion resistance	npd		
	4.21	Resistance to repeated opening and closing	4 (50.000) 3 (20.000)	[0960] – 23.00437.1 [0960] – 21.00400 rev A	2000x2700, 250 kg 2300x2700, 300/400 kg
	4.22	Behaviour between different climates	npd		
	4.23	Burglar resistance (AP version)	RC 2	[1136] – GSFM-23-051-01	See report



Characteristic			Performance		Notified body - Report	Tested size [mm]
Essential characteristics						
EN 14351-1	4.2	Resistance to wind load	B3 (1200 Pa) ⁽¹⁾ A3 (1200 Pa) ⁽¹⁾		[0960] – 11.1063 [0960] – 23.00690	1510x2616 ⁽³⁾ 1500x2700 ⁽³⁾
	4.5	Watertightness	7A (300 Pa) E750 (750 Pa)		[0960] – 11.1063 [0960] – 23.00690	1510x2616 1500x2700
	4.6	Dangerous substances	In the materials delivered by Reynaers, no dangerous substances as indicated in hEN 14351-1 are used.			
	4.7	Impact resistance	5		[0960] – SKG/HRU/cbo/10.0099-3	821x1729
	4.8	Load-bearing capacity of safety devices	npd			
	4.9	Height & width	See 6			
	4.11	Acoustic performance	Glass: 36 (-1;-5) 41 (-2;-4) 45 (-2;-6) 50 (-2;-8)	Sliding door: 34 (-1;-4) 38 (-1;-4) 42 (-1;-4) 45 (-1;-5)	[0749] – AC-23-050-02 [0749] – AC-23-050-03 [0749] – AC-23-050-10 * [0749] – AC-23-050-07 *	2705x2360
	4.12	Thermal transmittance	Ud to be calculated in function of the project. Uf-values are calculated under certification of BCCA: certificate BPCB-420-72-10077/2.			
	4.13	Radiation properties	These properties must be evaluated by the CE-label of the glass			
	4.14	Air permeability	4		[0960] – 11.1063 [0960] – 23.00690	1510x2616 1500x2700
Non-essential characteristics						
EN 14351-1	4.4.1	Reaction to fire	Anodized: A1 Painted: A2 Gaskets: E		EC decision 96/603/EC certificate EFR-21-001664A [0432] – 230006500-6	
	4.16	Operating forces	1		[0960] – 23.00437.1 [0960] – 21.00400 rev A	2000x2700, 250 kg 2300x2700, 300/400 kg
	4.17	Mechanical strength	4		[0960] – 18.00277.1 rev A	1510x2633, 171 kg
	4.18	Ventilation	npd			
	4.19	Bullet resistance (BP version)	npd			
	4.20	Explosion resistance	npd			
	4.21	Resistance to repeated opening and closing	4 (50.000) 3 (20.000)		[0960] – 23.00437.1 [0960] – 21.00400 rev A	2000x2700, 250 kg 2300x2700, 300/400 kg
	4.22	Behaviour between different climates	npd			
	4.23	Burglar resistance (AP version)	RC 2		[1136] – GSFM-23-051-01	See report

De prestaties van de producten die met bovenstaande unieke identificatiecodes zijn aangeduid, zijn in overeenstemming met de betreffende opgegeven prestaties. Deze prestatieverklaring wordt afgegeven onder de uitsluitende verantwoordelijkheid van raamSELECT
Voor en namens de fabrikant ondertekend door :


Naam en functie	Plaats en datum van afgifte	Handtekening
Stijn Hoskens (directeur)	01/07/2026	

<5.3> 3-RAIL HEFSCHUIFRAAM



raamSELECT NV
Merksplassesteenweg 18
2310 Rijkevorsel

Aangegeven prestaties volgens
NBN EN 14351-1:2006+A2:2016




Characteristic			Performance		Notified body - Report	Tested size [mm]
Essential characteristics						
EN 14351-1	4.2	Resistance to wind load	B3 (1200 Pa) ⁽¹⁾		[0960] – 16.00851	1514x2632 ⁽³⁾
	4.5	Watertightness	7A (300 Pa)		[0960] – 16.00851	1514x2632
	4.6	Dangerous substances	In the materials delivered by Reynaers, no dangerous substances as indicated in hEN 14351-1 are used.			
	4.7	Impact resistance	5		[0960] – SKG/HRU/cbo/10.0099-3	821x1729
	4.8	Load-bearing capacity of safety devices	npd			
	4.9	Height & width	See 6			
	4.11	Acoustic performance	Glass: 35 (-2;-6) 41 (-2;-4) 45 (-2;-6) 50 (-3;-8)	Sliding door: 34 (-1;-4) 37 (-1;-4) 39 (-1;-3) 39 (-1;-3)	[0960] – 11.156-Rev A	4090x2334
	4.12	Thermal transmittance	Ud to be calculated in function of the project. Uf-values are calculated under certification of BCCA: certificate BPCB-420-72-10077/2.			
	4.13	Radiation properties	These properties must be evaluated by the CE-label of the glass			
	4.14	Air permeability	4		[0960] – 16.00851	1514x2632

Non-essential characteristics					
EN 14351-1	4.4.1	Reaction to fire	Anodized: A1 Painted: A2 Gaskets: E	EC decision 96/603/EC certificate EFR-21-001664A [0432] – 230006500-6	
	4.16	Operating forces	2 1	[1488] – LK-02344/09/9/part 1 ⁽⁴⁾ [0960] – 21.00400 rev A	1101x2229, 66 kg 2300x2700, 300/400 kg
	4.17	Mechanical strength	4	[0960] – 18.00277.1 rev A	1510x2633, 171 kg
	4.18	Ventilation	Npd		
	4.19	Bullet resistance (BP version)	Npd		
	4.20	Explosion resistance	Npd		
	4.21	Resistance to repeated opening and closing	4 (50.000) 3 (20.000)	[0960] – 09.1125 ⁽⁴⁾ [0960] – 21.00400 rev A	1428x2219, 150 kg 2300x2700, 300/400 kg
	4.22	Behaviour between different climates	npd		
	4.23	Burglar resistance (AP version)	RC 2	[1136] – CAR 10257/3	See report

De prestaties van de producten die met bovenstaande unieke identificatiecodes zijn aangeduid, zijn in overeenstemming met de betreffende opgegeven prestaties. Deze prestatieverklaring wordt afgegeven onder de uitsluitende verantwoordelijkheid van raamSELECT

Voor en namens de fabrikant ondertekend door :


Naam en functie	Plaats en datum van afgifte	Handtekening
Stijn Hoskens (directeur)	01/07/2026	

<5.4> 4-RAIL HEFSCHUIFRAAM



raamSELECT NV
 Merksplassesteenweg 18
 2310 Rijkevorsel

Aangegeven prestaties volgens
NBN EN 14351-1:2006+A2:2016



Characteristic			Performance		Notified body - Report	Tested size [mm]
Essential characteristics						
EN 14351-1	4.2	Resistance to wind load	B2 (800 Pa) ⁽¹⁾		[0960] – 14.00700	1208x3000 ⁽³⁾
	4.5	Watertightness	4A (150 Pa)		[0960] – 14.00700	1208x3000
	4.6	Dangerous substances	In the materials delivered by Reynaers, no dangerous substances as indicated in hEN 14351-1 are used.			
	4.7	Impact resistance	5		[0960] – SKG/HRU/cbo/10.0099-3	821x1729
	4.8	Load-bearing capacity of safety devices	npd			
	4.9	Height & width	See 6			
	4.11	Acoustic performance	Glass: 35 (-2;-6) 41 (-2;-4) 45 (-2;-6) 50 (-3;-8)	Sliding door: 34 (-1;-4) 37 (-1;-4) 39 (-1;-3) 39 (-1;-3)	[0960] – 11.156-Rev A	4090x2334
	4.12	Thermal transmittance	Ud to be calculated in function of the project. Uf-values are calculated under certification of BCCA: certificate BPCB-420-72-10077/2.			
	4.13	Radiation properties	These properties must be evaluated by the CE-label of the glass			
	4.14	Air permeability	3		[0960] – 14.00700	1208x3000

Non-essential characteristics					
EN 14351-1	4.4.1	Reaction to fire	Anodized: A1 Painted: A2 Gaskets: E	EC decision 96/603/EC certificate EFR-21-001664A [0432] – 230006500-6	
	4.16	Operating forces	2	[1488] – LK-02344/09/9/part 1 ⁽⁴⁾	1101x2229, 66 kg
			1	[0960] – 21.00400 rev A	2300x2700, 300/400 kg
	4.17	Mechanical strength	4	[0960] – 18.00277.1 rev A	1510x2633, 171 kg
	4.18	Ventilation	npd		
	4.19	Bullet resistance (BP version)	npd		
	4.20	Explosion resistance	npd		
	4.21	Resistance to repeated opening and closing	4 (50.000) 3 (20.000)	[0960] – 09.1125 ⁽⁴⁾ [0960] – 21.00400 rev A	1428x2219, 150 kg 2300x2700, 300/400 kg
	4.22	Behaviour between different climates	npd		
	4.23	Burglar resistance (AP version)	npd		

De prestaties van de producten die met bovenstaande unieke identificatiecodes zijn aangeduid, zijn in overeenstemming met de betreffende opgegeven prestaties. Deze prestatieverklaring wordt afgegeven onder de uitsluitende verantwoordelijkheid van raamSELECT

Voor en namens de fabrikant ondertekend door :

Naam en functie	Plaats en datum van afgifte	Handtekening
Stijn Hoskens (directeur)	01/07/2026	